


Specifications

Force-velocity curves (DC bus voltage: 330 VDC)




Technical data for LMCB										
	Symbol	Unit	LMCB2	LMCB3	LMCB4	LMCB5	LMCB6	LMCB7	LMCB8	LMCBA
Forces and electrical parameters										
Continuous force at T _{max}	F _c	N	36	54	73	91	109	128	145	181
Continuous current at T _{max}	I _c	A _{eff}	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Peak force (for 1 s)	F _p	N	144	216	292	364	436	512	580	724
Peak current (for 1 s)	I _p	A _{eff}	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0
Force constant	K _f	N/A _{eff}	18.1	27.2	36.3	45.4	54.5	63.5	72.5	90.6
Electrical time constant	K _e	ms	0.4	0.4	0.4	0.4	0.4	0.3	0.3	0.3
Resistance ¹⁾	R ₂₅	Ω	3.6	5.4	7.1	9.0	10.7	12.6	14.6	17.9
Inductance ¹⁾	L	mH	1.4	1.9	2.6	3.2	3.8	4.4	5.0	6.2
Back EMF constant	K _u	V _{eff} /(m/s)	10.1	15.2	20.0	24.8	29.3	34.7	40.0	50.0
Motor constant	K _m	N/√W	7.7	9.5	11.2	12.4	13.6	14.7	15.5	17.5
Thermal resistance	R _{th}	°C/W	2.77	1.85	1.41	1.11	0.93	0.79	0.68	0.56
Thermal switch			3 PTC SNM 100 in series							
Max. DC bus voltage		V	330							
Mechanical parameters										
Max. bending radius of motor cable	R _{bend}	mm	37.5							
Pole pair pitch	2τ	mm	32							
Max. winding temperature	T _{max}	°C	100							
Mounting holes (forcer)	n		2	3	4	5	6	7	8	10
Weight of forcer	M _F	kg	0.20	0.29	0.38	0.48	0.58	0.68	0.72	0.88
Length of forcer	L _F	mm	66	98	130	162	194	226	258	322
Unit mass of stator	M _S	kg/m	12							
Length of stator/Dimension N	L _S	mm	128 mm/N = 2; 320 mm/N = 5							


All the specifications in the table (except dimensions) are in ± 10 % of tolerance at 25 °C ambient temperature

¹⁾ Line to line


Dimensions of forcer



Dimensions of stator



Mounting tolerances



LMCB motor cable assignment		
Motor cable	Signal	Diameter [mm]
Brown	U	7.5
White	V	
Grey	W	
Black	GND	
Yellow	T+	
Green	T-	