

X	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF:				LOCATION 																																																																																																													
	FLOOR OR SHOWER DRAINS WITH ADJUSTABLE STRAINER HEADS																																																																																																																	
	Load Rating: Light Duty having a Safe Live (Static) Load less than 2,000 lbs. (900 kg) per ASME A112.6.3 Floor Drain Standard. For the specific Safe Live Load rating of any grate, contact the Smith representative or factory direct.																																																																																																																	
	CAULK OUTLET Fig. 2010C (A) ROUND TOP Fig. 2010C (B) SQUARE TOP THREADED OUTLET Fig. 2015T (A) ROUND TOP Fig. 2015T (B) SQUARE TOP																																																																																																																	
<table border="1" style="width: 48%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Strainer Size</th> <th colspan="2">*Collar In High Position</th> <th colspan="2">*Collar In Low Position</th> <th colspan="2">Free Area SQ IN (SQ CM)</th> </tr> <tr> <th colspan="2">X</th> <th colspan="2">XX</th> <th>ROUND</th> <th>SQUARE</th> </tr> </thead> <tbody> <tr> <td>B</td> <td colspan="2">X</td> <td colspan="2">XX</td> <td></td> <td></td> </tr> <tr> <td>DIA or SQ</td> <td>MIN</td> <td>MAX</td> <td>MIN</td> <td>MAX</td> <td></td> <td></td> </tr> <tr> <td>05 (125)</td> <td>1 1/4 (32)</td> <td>2 1/4 (57)</td> <td>3/4 (19)</td> <td>1 5/8 (41)</td> <td>7 (45)</td> <td>6.5 (42)</td> </tr> <tr> <td>06 (150)</td> <td>1 1/4 (32)</td> <td>2 1/4 (57)</td> <td>3/4 (19)</td> <td>1 5/8 (41)</td> <td>9 (58)</td> <td>12.5 (81)</td> </tr> <tr> <td>07 (180)</td> <td>1 1/4 (32)</td> <td>2 1/4 (57)</td> <td>7/8 (22)</td> <td>1 7/8 (48)</td> <td>14 (90)</td> <td>11 (71)</td> </tr> <tr> <td>08 (205)</td> <td>1 1/2 (38)</td> <td>2 1/2 (64)</td> <td>1 (25)</td> <td>1 7/8 (48)</td> <td>17 (110)</td> <td>14 (90)</td> </tr> <tr> <td>•09 (230)</td> <td>1 1/2 (38)</td> <td>2 3/8 (60)</td> <td>1 (25)</td> <td>1 7/8 (48)</td> <td>18 (116)</td> <td>16 (103)</td> </tr> <tr> <td>•10 (255)</td> <td>1 1/2 (38)</td> <td>2 3/8 (60)</td> <td>1 (25)</td> <td>1 7/8 (48)</td> <td>23 (148)</td> <td>16 (103)</td> </tr> </tbody> </table> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th>A SIZE</th> <th>B</th> <th>D</th> <th>E</th> <th>F</th> <th>G</th> <th colspan="2">MIN-X-MAX</th> <th colspan="2">MIN-XX-MAX</th> </tr> </thead> <tbody> <tr> <td>02 (50)</td> <td>05 (125)</td> <td>3 1/4 (83)</td> <td>1 1/2 (38)</td> <td>4 3/4 (120)</td> <td>5 (125)</td> <td>1 1/4 (32)</td> <td>2 1/4 (57)</td> <td>3/4 (19)</td> <td>1 5/8 (41)</td> </tr> <tr> <td>03 (75)</td> <td>06 (150)</td> <td>2 3/4 (70)</td> <td>2 1/4 (57)</td> <td>4 3/4 (120)</td> <td>5 (125)</td> <td>1 1/4 (32)</td> <td>2 1/4 (57)</td> <td>3/4 (19)</td> <td>1 5/8 (41)</td> </tr> <tr> <td>04 (100)</td> <td>08 (200)</td> <td>3 1/4 (83)</td> <td>3 1/4 (83)</td> <td>6 (150)</td> <td>4 (100)</td> <td>1 1/2 (38)</td> <td>2 1/2 (64)</td> <td>-</td> <td>-</td> </tr> </tbody> </table>						Strainer Size	*Collar In High Position		*Collar In Low Position		Free Area SQ IN (SQ CM)		X		XX		ROUND	SQUARE	B	X		XX				DIA or SQ	MIN	MAX	MIN	MAX			05 (125)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	7 (45)	6.5 (42)	06 (150)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	9 (58)	12.5 (81)	07 (180)	1 1/4 (32)	2 1/4 (57)	7/8 (22)	1 7/8 (48)	14 (90)	11 (71)	08 (205)	1 1/2 (38)	2 1/2 (64)	1 (25)	1 7/8 (48)	17 (110)	14 (90)	•09 (230)	1 1/2 (38)	2 3/8 (60)	1 (25)	1 7/8 (48)	18 (116)	16 (103)	•10 (255)	1 1/2 (38)	2 3/8 (60)	1 (25)	1 7/8 (48)	23 (148)	16 (103)	A SIZE	B	D	E	F	G	MIN-X-MAX		MIN-XX-MAX		02 (50)	05 (125)	3 1/4 (83)	1 1/2 (38)	4 3/4 (120)	5 (125)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	03 (75)	06 (150)	2 3/4 (70)	2 1/4 (57)	4 3/4 (120)	5 (125)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	04 (100)	08 (200)	3 1/4 (83)	3 1/4 (83)	6 (150)	4 (100)	1 1/2 (38)	2 1/2 (64)	-	-
Strainer Size	*Collar In High Position		*Collar In Low Position		Free Area SQ IN (SQ CM)																																																																																																													
	X		XX		ROUND	SQUARE																																																																																																												
B	X		XX																																																																																																															
DIA or SQ	MIN	MAX	MIN	MAX																																																																																																														
05 (125)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	7 (45)	6.5 (42)																																																																																																												
06 (150)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	9 (58)	12.5 (81)																																																																																																												
07 (180)	1 1/4 (32)	2 1/4 (57)	7/8 (22)	1 7/8 (48)	14 (90)	11 (71)																																																																																																												
08 (205)	1 1/2 (38)	2 1/2 (64)	1 (25)	1 7/8 (48)	17 (110)	14 (90)																																																																																																												
•09 (230)	1 1/2 (38)	2 3/8 (60)	1 (25)	1 7/8 (48)	18 (116)	16 (103)																																																																																																												
•10 (255)	1 1/2 (38)	2 3/8 (60)	1 (25)	1 7/8 (48)	23 (148)	16 (103)																																																																																																												
A SIZE	B	D	E	F	G	MIN-X-MAX		MIN-XX-MAX																																																																																																										
02 (50)	05 (125)	3 1/4 (83)	1 1/2 (38)	4 3/4 (120)	5 (125)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)																																																																																																									
03 (75)	06 (150)	2 3/4 (70)	2 1/4 (57)	4 3/4 (120)	5 (125)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)																																																																																																									
04 (100)	08 (200)	3 1/4 (83)	3 1/4 (83)	6 (150)	4 (100)	1 1/2 (38)	2 1/2 (64)	-	-																																																																																																									
•Add 3/8" (10) to all min./max. dimensions for round strainer. •Not available for 05"(125) size strainer. *Collar is reversible to obtain extreme high and low strainer positions. REGULARLY FURNISHED: Duco Cast Iron Body with Flashing Collar and Adjustable Strainer Head with ADA Grate as Indicated by Suffix Letter Selected. Meets ASME Standard A112.6.3-2001 02(50), 03(75) or 04"(100) sizes only. SEE PM0457 FOR OPTIONAL STRAINER HEADS VARIATIONS: ☐ Ball Float Backwater Valve -BFV (Fig. 2015 only) ☐ Flapper Type Backwater Valve -V (NOTE 2) ☐ Hinged Grate -H (NOTE 1) ☐ Sediment Bucket -B ☐ Trap Primer Connection -P050 1/2" (13) & -P075 3/4" (19) ☐ Vandal Proof Screws -U ☐ Wide Flanged Strainer (Specify Fig. DX 2010) ☐ T Threaded Outlet ☐ Quad Close Trap Seal (Specify Fig. 2692) (Fig. 2010 Only) OPTIONAL MATERIALS: ☐ Bronze Body -BB (Fig. 2010 only) ☐ Chrome Plated Strainer -CP ☐ Galvanized Cast Iron Body -G ☐ Nickel Bronze Strainer -NB ☐ Polished Bronze Strainer -PB ☐ All Stainless Steel [Specify Fig. 9700-A (Fig. 2010 only)] ☐ Stainless Steel Strainers -SS [Available in 05(125) & 06(150) sizes only]																																																																																																																		
NOTE: Dimensions shown in parentheses are in millimeters.																																																																																																																		



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

P					NOTE 1: Sediment Bucket -B not provided for a Hinged Grate (-H) NOTE 2: Sediment Bucket -B not provided for a Ball Float (-BFV) or a Flapper Type (-V)																																																		
	OPTIONAL STRAINER HEADS																																																						
	ROUND STRAINER				FLAPPER TYPE BACKWATER VALVE																																																		
	MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB Stainless Steel Strainers -SS [Available in 05(125) & 06(150) sizes only] VARIATIONS: Hinged Grate (Specify Suffix -AH) (NOTE 1) Sediment Bucket -B Vandal Proof Screws -U <table border="1" style="width: 100%; font-size: 8px;"> <tr><th>B DIA</th><th>05 (125)</th><th>06 (150)</th><th>07 (180)</th><th>08 (205)</th><th>09 (230)</th><th>10 (255)</th></tr> <tr><td>H</td><td>2 (51)</td><td>2 (51)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td><td>2 1/2 (64)</td><td>2 3/4 (70)</td></tr> <tr><td>X MIN</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/2 (38)</td><td>1 1/2 (38)</td><td>1 1/2 (38)</td></tr> <tr><td>X MAX</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td><td>2 1/2 (64)</td><td>2 3/4 (70)</td></tr> </table> SUFFIX -A Specify Type, Size & Finish eg: A05NB				B DIA	05 (125)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)	X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)	X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)	MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: *Hinged Grate (Specify Suffix -AH) Vandal Proof Screws -U <table border="1" style="width: 100%; font-size: 8px;"> <tr><th>B DIA</th><th>05 (125)</th><th>06 (150)</th><th>07 (180)</th><th>08 (205)</th></tr> <tr><td>H</td><td>2 (51)</td><td>2 (51)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td></tr> <tr><td>X MIN</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/2 (38)</td></tr> <tr><td>X MAX</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td></tr> </table> SUFFIX -AV Specify Type, Size & Finish eg: AV05NB *Not available for 05" (125) size				B DIA	05 (125)	06 (150)	07 (180)	08 (205)	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)
B DIA	05 (125)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)																																																	
H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)																																																	
X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)																																																	
X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)																																																	
B DIA	05 (125)	06 (150)	07 (180)	08 (205)																																																			
H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)																																																			
X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)																																																			
X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)																																																			
SQUARE STRAINER				STRAINER HEAD w/SQUARE HINGED COVER																																																			
MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -BV) 05 (125), 06 (150), 07 (180) or 08" (205) sizes only (NOTE 2) Hinged Grate (Specify Suffix -BH) (NOTE 1) Sediment Bucket -B Vandal Proof Screws -U <table border="1" style="width: 100%; font-size: 8px;"> <tr><th>B SQ</th><th>05 (125)</th><th>06 (150)</th><th>07 (180)</th><th>08 (205)</th><th>09 (230)</th><th>10 (255)</th></tr> <tr><td>H</td><td>2 (51)</td><td>2 (51)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td></tr> <tr><td>X MIN</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/2 (38)</td><td>1 1/2 (38)</td><td>1 1/2 (38)</td></tr> <tr><td>X MAX</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td><td>2 1/4 (57)</td><td>2 3/8 (60)</td></tr> </table> SUFFIX -B Specify Type, Size & Finish eg: B05NB				B SQ	05 (125)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	2 1/4 (57)	X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)	X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	2 3/8 (60)	MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Gasketed Water Tight Cover -GC Secured Cover -SC Secondary Strainer Grate-SG SUFFIX -BS Specify Type, Size & Finish eg: BSNB																							
B SQ	05 (125)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)																																																	
H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	2 1/4 (57)																																																	
X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)																																																	
X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	2 3/8 (60)																																																	
REINFORCED ROUND STRAINER				REINFORCED TRACTOR STRAINER																																																			
MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -CV) (NOTE 2) Sediment Bucket -B Vandal Proof Screws -U <table border="1" style="width: 100%; font-size: 8px;"> <tr><th>B DIA</th><th>05 (125)</th><th>06 (150)</th><th>08 (205)</th><th>10 (255)</th></tr> <tr><td>H</td><td>2 (51)</td><td>2 (51)</td><td>2 1/2 (64)</td><td>2 3/4 (70)</td></tr> <tr><td>MIN</td><td>1 1/4 (32)</td><td>1 1/4 (32)</td><td>1 1/2 (38)</td><td>1 7/8 (48)</td></tr> <tr><td>MAX</td><td>2 1/4 (57)</td><td>2 1/4 (57)</td><td>2 1/2 (64)</td><td>2 3/4 (70)</td></tr> </table> SUFFIX -C Specify Type, Size & Finish eg: C06NB				B DIA	05 (125)	06 (150)	08 (205)	10 (255)	H	2 (51)	2 (51)	2 1/2 (64)	2 3/4 (70)	MIN	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 7/8 (48)	MAX	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 3/4 (70)	MATERIALS: Cast Iron -CI Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -DV or -EV) (NOTE 2) Sediment Bucket -B Vandal Proof Screws -U <table border="1" style="width: 100%; font-size: 8px;"> <tr><th>SUFFIX</th><th>B DIA</th><th>H</th><th colspan="2">X</th></tr> <tr><td>-D</td><td>07 (180)</td><td>3 1/4 (83)</td><td>2 5/8 (67)</td><td>3 1/2 (89)</td></tr> <tr><td>-E</td><td>09 (230)</td><td>3 1/2 (89)</td><td>2 3/4 (70)</td><td>3 1/2 (89)</td></tr> </table> SUFFIX -D-E Specify Type, Size & Finish eg: D07PB E09PB				SUFFIX	B DIA	H	X		-D	07 (180)	3 1/4 (83)	2 5/8 (67)	3 1/2 (89)	-E	09 (230)	3 1/2 (89)	2 3/4 (70)	3 1/2 (89)													
B DIA	05 (125)	06 (150)	08 (205)	10 (255)																																																			
H	2 (51)	2 (51)	2 1/2 (64)	2 3/4 (70)																																																			
MIN	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 7/8 (48)																																																			
MAX	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 3/4 (70)																																																			
SUFFIX	B DIA	H	X																																																				
-D	07 (180)	3 1/4 (83)	2 5/8 (67)	3 1/2 (89)																																																			
-E	09 (230)	3 1/2 (89)	2 3/4 (70)	3 1/2 (89)																																																			
TILE FLANGE				ADJUSTABLE STRAINER HEAD																																																			
MATERIALS: Chrome Plated -CP Polished Bronze -PB Nickel Bronze -NB VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -FV) (NOTE 2) Holes in Flange -SH Sediment Bucket -B Vandal Proof Screws -U <table border="1" style="width: 100%; font-size: 8px;"> <tr><th colspan="2">X</th></tr> <tr><td>MIN</td><td>1 1/4 (32)</td></tr> <tr><td>MAX</td><td>2 1/8 (54)</td></tr> </table> SUFFIX -F Specify Type, Size & Finish eg: F06NB				X		MIN	1 1/4 (32)	MAX	2 1/8 (54)	VARIATIONS: Flapper Type Backwater Valve (Specify Suffix -F37V or F38V) (NOTE 2) Sediment Bucket -B MATERIALS: Cast Iron -CI Chrome Plated -CP Galvanized Cast Iron -G Polished Bronze -PB Nickel Bronze -NB <table border="1" style="width: 100%; font-size: 8px;"> <tr><th>SUFFIX</th><th>-F37</th><th>-F38</th></tr> <tr><td>B DIA</td><td>07 (180)</td><td>09 (230)</td></tr> <tr><td>H</td><td>3 1/4 (83)</td><td>3 1/2 (89)</td></tr> <tr><td>X MIN</td><td>2 5/8 (67)</td><td>2 3/4 (70)</td></tr> <tr><td>X MAX</td><td>3 1/2 (89)</td><td>3 1/2 (89)</td></tr> </table> SUFFIX -F37-F38 Specify Type, Size & Finish eg: F37NB F38CP				SUFFIX	-F37	-F38	B DIA	07 (180)	09 (230)	H	3 1/4 (83)	3 1/2 (89)	X MIN	2 5/8 (67)	2 3/4 (70)	X MAX	3 1/2 (89)	3 1/2 (89)																											
X																																																							
MIN	1 1/4 (32)																																																						
MAX	2 1/8 (54)																																																						
SUFFIX	-F37	-F38																																																					
B DIA	07 (180)	09 (230)																																																					
H	3 1/4 (83)	3 1/2 (89)																																																					
X MIN	2 5/8 (67)	2 3/4 (70)																																																					
X MAX	3 1/2 (89)	3 1/2 (89)																																																					
<table border="1" style="width: 100%; font-size: 10px;"> <tr> <td rowspan="3" style="width: 30px; text-align: center; vertical-align: middle;">FIGURE NUMBER</td> <td style="width: 30px; text-align: center;">P</td> <td style="width: 100px; text-align: center;">12-24-24</td> <td rowspan="3" style="width: 150px; text-align: center; vertical-align: middle;">Rev. Notes Removed Function, Rev. Var. Added NOTE 1 & 2</td> <td style="width: 30px; text-align: center;">HS</td> <td style="width: 30px; text-align: center;">KV</td> <td rowspan="3" style="width: 100px; text-align: center; vertical-align: middle;">FIGURE NUMBER 2005/2010 SERIES OPTIONAL STRAINER HEADS 1 OF 2</td> </tr> <tr> <td style="text-align: center;">N</td> <td style="text-align: center;">5-21-24</td> <td style="text-align: center;">HS</td> <td style="text-align: center;">KV</td> </tr> <tr> <td style="text-align: center;">M</td> <td style="text-align: center;">10-8-21</td> <td style="text-align: center;">KK</td> <td style="text-align: center;">JM</td> </tr> <tr> <td style="text-align: center;">REV.</td> <td style="text-align: center;">DATE</td> <td style="text-align: center;">DESCRIPTION</td> <td style="text-align: center;">BY</td> <td style="text-align: center;">CKD. BY</td> <td colspan="2"></td> </tr> </table>								FIGURE NUMBER	P	12-24-24	Rev. Notes Removed Function, Rev. Var. Added NOTE 1 & 2	HS	KV	FIGURE NUMBER 2005/2010 SERIES OPTIONAL STRAINER HEADS 1 OF 2	N	5-21-24	HS	KV	M	10-8-21	KK	JM	REV.	DATE	DESCRIPTION	BY	CKD. BY																												
FIGURE NUMBER	P	12-24-24	Rev. Notes Removed Function, Rev. Var. Added NOTE 1 & 2	HS	KV	FIGURE NUMBER 2005/2010 SERIES OPTIONAL STRAINER HEADS 1 OF 2																																																	
	N	5-21-24		HS	KV																																																		
	M	10-8-21		KK	JM																																																		
REV.	DATE	DESCRIPTION	BY	CKD. BY																																																			

NOTE: Dimensions shown in parentheses are in millimeters.



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

