

D	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com MEMBER OF: MEMBER OF:				LOCATION 																																																																																									
	FLOOR DRAIN WITH INTEGRAL TRAP																																																																																													
	 Aux. Inlet #1 (When Specified) 6 (150) Aux. Inlet #2 (When Specified) Aux. Inlet #3 (When Specified) Outlet A Low Position XX- Min Max High Position X- Min Max Seepage Openings Reversible Collar (Flashing Clamp) NO-HUB Outlet (Regularly Furnished) 1"(25) NPT Cleanout Plug 2 (51) 9 (230) 7 1/2 (190) 5 1/2 (140) B D A E																																																																																													
	AVAILABLE STRAINERS <table border="1" style="width: 100%; border-collapse: collapse; font-size: 0.8em;"> <thead> <tr> <th rowspan="2">Strainer Size</th> <th colspan="2">*Collar In High Position</th> <th colspan="2">*Collar In Low Position</th> <th colspan="2">Free Area Sq. In. (Sq. Cm.)</th> <th rowspan="2">H MIN</th> </tr> <tr> <th>Min.</th> <th>Max.</th> <th>Min.</th> <th>Max.</th> <th>Round</th> <th>Square</th> </tr> </thead> <tbody> <tr> <td>B</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Dia. or Sq.</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>05 (125)</td> <td>1 1/4 (32)</td> <td>2 1/4 (57)</td> <td>3/4 (19)</td> <td>1 5/8 (41)</td> <td>7 (45.16)</td> <td>6.5 (41.94)</td> <td>8 1/4 (210)</td> </tr> <tr> <td>06 (150)</td> <td>1 1/4 (32)</td> <td>2 1/4 (57)</td> <td>3/4 (19)</td> <td>1 5/8 (41)</td> <td>9 (58.07)</td> <td>12.5 (80.65)</td> <td></td> </tr> <tr> <td>07 (180)</td> <td>1 1/4 (32)</td> <td>2 1/4 (57)</td> <td>7/8 (22)</td> <td>1 7/8 (48)</td> <td>14 (90.33)</td> <td>11 (70.97)</td> <td>8 3/8 (213)</td> </tr> <tr> <td>08 (205)</td> <td>1 1/2 (38)</td> <td>2 1/2 (63)</td> <td>1 (25)</td> <td>1 7/8 (48)</td> <td>17 (109.68)</td> <td>14 (90.33)</td> <td></td> </tr> <tr> <td>• 09 (230)</td> <td>1 1/2 (38)</td> <td>2 3/8 (60)</td> <td>1 (25)</td> <td>1 7/8 (48)</td> <td>18 (116.14)</td> <td>16 (103.23)</td> <td>8 1/2 (215)</td> </tr> <tr> <td>• 10 (255)</td> <td>1 1/2 (38)</td> <td>2 3/8 (60)</td> <td>1 (25)</td> <td>1 7/8 (48)</td> <td>23 (148.40)</td> <td>16 (103.23)</td> <td></td> </tr> </tbody> </table> • Add 3/8"(10) To All Min./Max. Dimensions For Round Strainer. *Collar is reversible to obtain extreme high and low strainer positions. <table border="1" style="width: 100%; border-collapse: collapse; font-size: 0.8em;"> <thead> <tr> <th>A PIPE SIZE</th> <th>D</th> <th>E</th> </tr> </thead> <tbody> <tr> <td>02 (50)</td> <td>3 3/16 (80)</td> <td>2 5/16 (58.67)</td> </tr> <tr> <td>03 (76)</td> <td>3 11/16 (93)</td> <td>3 3/8 (85.95)</td> </tr> <tr> <td>04 (100)</td> <td>4 3/16 (106)</td> <td>4 3/8 (111)</td> </tr> </tbody> </table>					Strainer Size	*Collar In High Position		*Collar In Low Position		Free Area Sq. In. (Sq. Cm.)		H MIN	Min.	Max.	Min.	Max.	Round	Square	B								Dia. or Sq.								05 (125)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	7 (45.16)	6.5 (41.94)	8 1/4 (210)	06 (150)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	9 (58.07)	12.5 (80.65)		07 (180)	1 1/4 (32)	2 1/4 (57)	7/8 (22)	1 7/8 (48)	14 (90.33)	11 (70.97)	8 3/8 (213)	08 (205)	1 1/2 (38)	2 1/2 (63)	1 (25)	1 7/8 (48)	17 (109.68)	14 (90.33)		• 09 (230)	1 1/2 (38)	2 3/8 (60)	1 (25)	1 7/8 (48)	18 (116.14)	16 (103.23)	8 1/2 (215)	• 10 (255)	1 1/2 (38)	2 3/8 (60)	1 (25)	1 7/8 (48)	23 (148.40)	16 (103.23)		A PIPE SIZE	D	E	02 (50)	3 3/16 (80)	2 5/16 (58.67)	03 (76)	3 11/16 (93)	3 3/8 (85.95)	04 (100)	4 3/16 (106)
Strainer Size	*Collar In High Position		*Collar In Low Position		Free Area Sq. In. (Sq. Cm.)		H MIN																																																																																							
	Min.	Max.	Min.	Max.	Round	Square																																																																																								
B																																																																																														
Dia. or Sq.																																																																																														
05 (125)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	7 (45.16)	6.5 (41.94)	8 1/4 (210)																																																																																							
06 (150)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	9 (58.07)	12.5 (80.65)																																																																																								
07 (180)	1 1/4 (32)	2 1/4 (57)	7/8 (22)	1 7/8 (48)	14 (90.33)	11 (70.97)	8 3/8 (213)																																																																																							
08 (205)	1 1/2 (38)	2 1/2 (63)	1 (25)	1 7/8 (48)	17 (109.68)	14 (90.33)																																																																																								
• 09 (230)	1 1/2 (38)	2 3/8 (60)	1 (25)	1 7/8 (48)	18 (116.14)	16 (103.23)	8 1/2 (215)																																																																																							
• 10 (255)	1 1/2 (38)	2 3/8 (60)	1 (25)	1 7/8 (48)	23 (148.40)	16 (103.23)																																																																																								
A PIPE SIZE	D	E																																																																																												
02 (50)	3 3/16 (80)	2 5/16 (58.67)																																																																																												
03 (76)	3 11/16 (93)	3 3/8 (85.95)																																																																																												
04 (100)	4 3/16 (106)	4 3/8 (111)																																																																																												
REGULARLY FURNISHED: Duco Cast Iron Body with Integral Trap and 1"(25) NPT Plug and Flashing Collar and Adjustable Strainer Head as Indicated by Suffix Letter Selected. VARIATIONS: ☐ One to Three Side Auxiliary Inlets 1/2"(13) thru 2"(51) Tap, NPT or B.S. (Specify size, qty. and location) ☐ Vandal Resistant -U OPTIONAL MATERIALS: ☐ Chrome Plated Strainer -CP (Not recommended for traffic floor) ☐ Galvanized Body -G ☐ High Polished Nickel Bronze -NB -HPF ☐ Satin Polished Bronze Strainer -PB ☐ Nickel Bronze Strainer -NB																																																																																														
NOTE: Dimensions Shown in Parenthesis are in Millimeters.																																																																																														
FIGURE NUMBER	<table border="1" style="width: 100%; border-collapse: collapse; font-size: 0.7em;"> <tr> <td style="width: 10%;">D</td> <td style="width: 15%;">11-4-11</td> <td style="width: 25%;">Rev. Reg. Furn., Opt. Mat.</td> <td style="width: 10%;">TBW</td> <td style="width: 10%;">CL</td> <td style="width: 10%;">WEIGHT POUNDS</td> <td style="width: 10%;">VOLUME CUBIC FEET</td> <td style="width: 15%;">FIGURE NUMBER</td> </tr> <tr> <td>C</td> <td>10-31-97</td> <td>Submittal Update</td> <td>EMB</td> <td>BS</td> <td></td> <td></td> <td rowspan="3" style="text-align: center; font-size: 1.5em; font-weight: bold;">2095</td> </tr> <tr> <td>B</td> <td>12-28-95</td> <td>Added Dim</td> <td>EMB</td> <td>SB</td> <td></td> <td></td> </tr> <tr> <td>A</td> <td>1-16-95</td> <td>Revised</td> <td>EMB</td> <td>JCS</td> <td></td> <td></td> </tr> <tr> <td>REV.</td> <td>DATE</td> <td>DESCRIPTION</td> <td>BY</td> <td>CKD. BY</td> <td></td> <td></td> <td></td> </tr> </table>				D	11-4-11	Rev. Reg. Furn., Opt. Mat.	TBW	CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER	C	10-31-97	Submittal Update	EMB	BS			2095	B	12-28-95	Added Dim	EMB	SB			A	1-16-95	Revised	EMB	JCS			REV.	DATE	DESCRIPTION	BY	CKD. BY																																																							
	D	11-4-11	Rev. Reg. Furn., Opt. Mat.	TBW	CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER																																																																																						
C	10-31-97	Submittal Update	EMB	BS			2095																																																																																							
B	12-28-95	Added Dim	EMB	SB																																																																																										
A	1-16-95	Revised	EMB	JCS																																																																																										
REV.	DATE	DESCRIPTION	BY	CKD. BY																																																																																										