

R						LOCATION											
	FLOOR DRAINS WITH 8 1/2" (215) ROUND TOPS																
DRAWING NUMBER S2110	MEDIUM DUTY DRAINS Load Rating: Medium Duty having a Safe Live (Static) Load between 2,000 lbs. (900 kg) and 4,999 lbs. (2,250 kg) per ASME A112.6.3 Floor Drain Standard. For the specific Safe Live Load rating of any grate, contact the Smith representative or factory direct. Free Area 14.25 SQ IN (92) SQ CM																
SIZE A																	
SCALE: NONE																	
DATE: 5-17-85	☐ Fig. 2110C ... CAULK OUTLET ☐ Fig. 2110T ... THREADED OUTLET ☐ Fig. 2110Y ... NO-HUB OUTLET ☐ Fig. 2115C ... CAULK OUTLET ☐ Fig. 2115T ... THREADED OUTLET																
APPROVED BY: TD	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>A SIZE</th> <td>02 (50)</td> <td>03 (75)</td> <td>04 (100)</td> <td>05 (125), 06 (150)</td> </tr> <tr> <th>B</th> <td colspan="2">3 3/4 (95) for Caulk, NO-HUB, and Speedi-Set®, 2 (51) for Threaded</td> <td colspan="2">3 3/4 (95) NO-HUB Only</td> </tr> </table>							A SIZE	02 (50)	03 (75)	04 (100)	05 (125), 06 (150)	B	3 3/4 (95) for Caulk, NO-HUB, and Speedi-Set®, 2 (51) for Threaded		3 3/4 (95) NO-HUB Only	
A SIZE	02 (50)	03 (75)	04 (100)	05 (125), 06 (150)													
B	3 3/4 (95) for Caulk, NO-HUB, and Speedi-Set®, 2 (51) for Threaded		3 3/4 (95) NO-HUB Only														
CHECKED BY: TD	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>A SIZE</th> <td>02 (50)</td> <td>03 (75)</td> <td>04 (100)</td> </tr> <tr> <th>B</th> <td>4 1/4 (110)</td> <td>3 3/4 (95)</td> <td>3 1/4 (83)</td> </tr> </table>							A SIZE	02 (50)	03 (75)	04 (100)	B	4 1/4 (110)	3 3/4 (95)	3 1/4 (83)		
A SIZE	02 (50)	03 (75)	04 (100)														
B	4 1/4 (110)	3 3/4 (95)	3 1/4 (83)														
DRAWN BY: PJ	REGULARLY FURNISHED: Duco Cast Iron Body and Flashing Collar with Cast Iron Slotted ADA Grate. VARIATIONS: ☐ Closure Plug -XP (Fig. 2110 only) ☐ Dome Grate -D ☐ Flat Bottom Strainer -FBS (Fig. 2110 only) ☐ L Speedi-Set® Service Weight (Fig. 2110 only) ☐ 2(50), 3(75) & 4"(100) sizes only ☐ LXH Speedi-Set® Extra Heavy (Fig. 2110 only) ☐ 2(50), 3(75) & 4"(100) sizes only ☐ NO-HUB Adaptor (Specify Fig. 2646Y) (Fig. 2115 only) ☐ Sediment Bucket -B ☐ Square Top -S ☐ Trap Primer Connection -P050 1/2"(13) & -P075 3/4"(19) ☐ Vandal Proof Grate -U ☐ Wide Flange Deck Drain (Specify Fig. DX2565) ☐ Quad Close Trap Seal (Specify Fig. 2692) (Fig. 2110 Only) ☐ Heel Proof Grate -Q45 OPTIONAL MATERIALS: ☐ Ductile Iron Grate -M ☐ Galvanized Cast Iron -G ☐ Nickel Bronze Top -NB ☐ Polished Bronze Top -PB ☐ Stainless Steel (Specify Fig. 9710)																
FIGURE NUMBER 2110, 2115	△ Add 3/16" (5) when bronze top is specified. *This dimension to internal stop of Speedi-Set® gasket. **Meets U.S. Gov't Spec. per WW-P-541-b, Type 220, 02 (50) and 03" (75) sizes only. See Fig. 2130 for 04" (100) size. Meets ANSI Spec A112.6.3-2001 02(50), 03(75) or 04"(100) sizes only. ▲ Not available on Fig. 2110T threaded outlet drain. NOTE: Dimensions shown in parentheses are in millimeters.																
REV.	DATE	DESCRIPTION			BY	CKD. BY	FIGURE NUMBER 2110, 2115										



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov