

R	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: LOCATION				
	FLOOR DRAINS 8 1/2" (215) ROUND TOPS				
DRAWING NUMBER	s2120				
SIZE	A				
SCALE:	NONE				
DATE:	5-17-85				
APPROVED BY:	TD				
CHECKED BY:	TD				
DRAWN BY:	PJ				
FIGURE NUMBER	2120, 2125				

ΔAdd 1/8" (3) when bronze top is specified.
*This dimension to internal stop of Speedi-Set® gasket.

☐ Fig. 2120C.....CAULK OUTLET

☐ Fig. 2120Y.....NO-HUB OUTLET

☐ Fig. 2120T.....THREADED OUTLET

☐ Fig. 2125C.....CAULK OUTLET

☐ Fig. 2125T.....THREADED OUTLET

A SIZE	02 (50)	03 (75)	04 (100)	05(125), 06 (150)
B	3 3/4 (95) for Caulk, NO-HUB, and Speedi-Set®, 2 (51) for Threaded		3 3/4 (95) NO-HUB Only	

REGULARLY FURNISHED:
Ducto Cast Iron Body and Flashing Collar with Medium Duty Cast Iron ADA Tractor Grate.

****For Heavy Duty:** Specify Ductile Iron Grate-M.

VARIATIONS:

- ☐ Closure Plug -XP (Fig. 2110 only)
- ☐ Dome Grate -D
- ☐ Flat Bottom Strainer -FBS (Fig. 2120 only)
- ☐ L Speedi-Set® Service Weight (Fig. 2120 only)
- ☐ LXH Speedi-Set® Extra Heavy (Fig. 2120 only)
- ☐ NO-HUB Adaptor (Specify Fig. 2646Y) (Fig. 2125 only)
- ☐ Sediment Bucket -B
- ☐ Square Top -S
- ▲ ☐ Trap Primer Connection -P050 1/2" (13) & -P075 3/4" (19)
- ☐ Vandal Proof Grate -U
- ☐ Heel Proof Grate -Q45
- ☐ Quad Close Trap Seal (Specify Fig. 2692) (Fig. 2120 Only)

OPTIONAL MATERIALS:

- ** ☐ Ductile Iron Grate -M
- ☐ Galvanized Cast Iron -G
- ☐ Nickel Bronze Top -NB
- ☐ Polished Bronze Top -PB

NOTE: Dimensions shown in parentheses are in millimeters.
▲ Not available on Fig. 2120T threaded outlet drain.

R	7-15-24	Rev. Variations and Opt. Mat Added @ to "Speedi-Set"	HS	KV	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER
Q	3-10-23	Added @ to "Speedi-Set"	KK	CL			2120, 2125
P	1-23-23	Added ADA	KK	JT			
N	5-27-21	Rem. Note & Added to Reg. Fur.	KK	JT			
REV.	DATE	DESCRIPTION	BY	CKD. BY			