

L

DRAWING NUMBER
S2210

SIZE
A

SCALE:
NONE

DATE:
5-17-85

APPROVED BY:
TD

CHECKED BY:
TD

DRAWN BY:
CMB

2210, 2215

FIGURE
NUMBER

SMITH® JAY R. SMITH MFG. CO.®
MEMBER OF MORRIS GROUP INTERNATIONAL
POST OFFICE BOX 3237
MONTGOMERY, ALABAMA 36109-0237 (USA)
TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com

ASPE

MEMBER OF:

LOCATION

FLOOR DRAINS
WITH 8 1/2" (215) ROUND TOPS AND SEDIMENT BUCKETS
"SAFE-SET"® BUCKET

Load Rating: Light Duty having a Safe Live (Static) Load less than 2,000 lbs. (900 kg) per ASME A112.6.3 Floor Drain Standard.
For the specific Safe Live Load rating of any grate, contact the Smith representative or factory direct.

Free Area
9.25 SQ IN
(60) SQ CM

8 1/2 (215) DIA

8 (205) DIA

6 1/2 (165) DIA

3 3/4 (95)

ΔB

A

Fig. 2210C. . . . CAULK OUTLET

Fig. 2210Y. . . . NO-HUB OUTLET

8 1/2 (215) DIA

8 (205) DIA

6 1/2 (165) DIA

2 1/2" (64) Deep Slotted Sediment Bucket

Auxiliary Drainage Openings

ΔB

A

Δ 6 1/2 (165)

4 3/4 (120)

5 1/2 (140)

Fig. 2215C. . . . CAULK OUTLET

Fig. 2215T. . . . THREADED OUTLET

A SIZE	02 (50)	03 (75)	04 (100)
B	5 (125) for Caulk, NO-HUB and Speedi-Set® 3 1/2 (89) for Threaded		

A SIZE	02 (50)	03 (75)	04 (100)
B	4 3/4 (120)	4 1/4 (110)	3 3/4 (95)

REGULARLY FURNISHED:
Duct Cast Iron Body with Cast Iron ADA Grate and Sediment Bucket.

*This Dimension to Internal Stop of Speedi-Set® Gasket.
Δ Add 1/4" (6) when bronze top is specified

VARIATIONS:

☐ Dome Grate -D

☐ Hinged Grate -H

☐ L Speedi-Set® Service Weight (Fig. 2210 only)

☐ LXH Speedi-Set® Extra Heavy (Fig. 2210 only)

☐ NO-HUB Adaptor (Specify Fig. 2646Y) (Fig. 2215 only)

☐ Square Top -S

☐ Trap Primer Connection -P050 1/2" (13) & -P075 3/4" (19)

☐ Vandal Proof Grate -U

☐ Wide Flange Deck Drain (Specify Fig. DX2565)

☐ T Threaded Outlet

☐ Quad Close Trap Seal (Specify Fig. 2692) (Fig. 2210 Only)

OPTIONAL MATERIALS:

☐ Ductile Iron Bucket and Grate -MGB

☐ Galvanized Cast Iron -G

☐ Nickel Bronze Top -NB

☐ Polished Bronze Top -PB

NOTE: Dimensions shown in parentheses are in millimeters.

L
K
J
H

8-10-23
2-23-23
1-23-23
7-22-19

Removed Function
Added "®" to "Speedi-Set"
Added ADA
Added Load Rating

HS
KK
KK
MW

CL
CL
JT
JM

WEIGHT
POUNDS

VOLUME
CUBIC FEET

FIGURE NUMBER
2210, 2215

REV.

DATE

DESCRIPTION

BY

CKD. BY

WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA

DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE

!

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov