

L	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: LOCATION			
	TRAFFIC FLOOR DRAINS			
	LARGE CAPACITY SEDIMENT BUCKET			
	<u>Cast Iron Grate</u> Load Rating: Medium Duty having a Safe Live (Static) Load between 2,000 lbs. (900 kg) and 4,999 lbs. (2,250 kg) per ASME A112.6.3 Floor Drain Standard. For the specific Safe Live Load rating of any grate, contact the Smith representative or factory direct. <u>Ductile Iron Grate</u> Load Rating: Heavy Duty having a Safe Live (Static) Load between 5,000 lbs. (2,250 kg) and 7,499 lbs. (3,375 kg) per ASME A112.6.3 Floor Drain Standard. For the specific Safe Live Load rating of any grate, contact the Smith representative or factory direct.			
DRAWING NUMBER	S2450			
SIZE	A			
SCALE:	NONE			
DATE:	5-17-85			
APPROVED BY:	TD			
CHECKED BY:	TD			
DRAWN BY:	PJ			
2450, 2455	REGULARLY FURNISHED: Fabricated Steel Body with Galvanized Coating Inside and Outside and Cast Iron Grate and Stainless Steel Ported Bucket, with Mesh Screen and Lift Bar. VARIATIONS: ☐ Flashing Clamp -C ☐ Flat Bottom Strainer -FBS (Fig. 2450 only) ☐ Stainless Steel Perforated Bucket -SSB ☐ T Threaded Outlet ☐ Quad Close Trap Seal (Specify Fig. 2692) (Fig. 2450 Only) ☐ Trap Primer Connection -P050 1/2"(13) & -P075 3/4"(19) OPTIONAL MATERIALS: ☐ Ductile Iron Grate -M ☐ Nickel Bronze Top -NB ☐ Polished Bronze Top -PB			
Δ add 1/8" (3) when bronze top is specified.				
NOTE: Dimensions shown in parentheses are in millimeters.				
REV.	DATE	DESCRIPTION	BY	CKD. BY
L K H	1-8-24 9-6-19 7-24-19 6-18-19	Revised Variations Rev.Δ, Pipe Size, Var./ Add No-Hub Added Load Rating Removed Function	HS MW MW MW	CB CL JM JM
WEIGHT POUNDS		VOLUME CUBIC FEET		FIGURE NUMBER
				2450, 2455



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov