

H	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:				LOCATION 				
	SPECIAL PURPOSE DRAINS								
DRAWING NUMBER S2585	SIZE A	SCALE: NONE	DATE: 5-17-85	APPROVED BY: TD	CHECKED BY: TD	DRAWN BY: PJ	DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE		
GUTTER DRAINS									
Free Area 21.5 SQ IN (139) SQ CM 15 3/4(400) x 8 1/4(210) 13 1/4(335) x 5 3/4(145) 12 1/2(324) x 5(125) Δ2(51) *Δ5 3/4 (145) A Secured Grate Seepage Openings (When Specified or when used with Flashing Clamp) Flashing Clamp (When Specified) A (Pipe Size) = 02(50), 03(75), or 04(100) Fig. 2585C CAULK OUTLET Fig. 2585T THREADED OUTLET Fig. 2585Y NO-HUB OUTLET Δ add 7/16"(11) when bronze top is specified. *5"(125) for threaded outlet. REGULARLY FURNISHED: Duco Cast Iron Body with Secured ADA Grate. VARIATIONS: Flashing Clamp -C Less Grate -LG Vandal Proof Grate -U Quad Close Trap Seal (Specify Fig. 2692) OPTIONAL MATERIALS: Ductile Iron Grate -M Galvanized Cast Iron -G Nickel Bronze Top -NB Polished Bronze Top -PB									
NOTE: Dimensions shown in parentheses are in millimeters.									
2585	FIGURE NUMBER	H G F E	9-22-23 8-10-23 1-23-23 7-8-15	Revised Fig Options/Variations Removed Function Added ADA Revised Variations	HS HS KK TBW	CB CL JT CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 2585
REV.	DATE	DESCRIPTION			BY	CKD. BY			