

FIGURE NUMBER 3510, 3515	DRAWN BY: CM	CHECKED BY: JD	APPROVED BY: SJM	DATE: 9-19-85	SCALE: NONE	SIZE A	DRAWING NUMBER S3510	H																																										
	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:								LOCATION																																									
	FUNNEL-CEPTOR® INDIRECT WASTE DRAINS WITH ADJUSTABLE STRAINER HEADS																																																	
	Conforms to ASME A112.6.7/CSA B79.7																																																	
	BOTTOM OUTLET SIDE OUTLET ☐ Fig. 3510C ... CAULK OUTLET ☐ Fig. 3510T ... THREADED OUTLET ☐ Fig. 3510Y ... NO-HUB OUTLET <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <th>A SIZE</th> <td>02 (50)</td> <td>03 (75)</td> <td>04 (100)</td> </tr> <tr> <th>B</th> <td colspan="3">4 (100) for Caulk, NO-HUB and Speedi-Set® 3 (76) for Threaded</td> </tr> </table> ☐ Fig. 3515T ... THREADED OUTLET <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <th>A</th> <th>B</th> <th>C</th> <th>D</th> </tr> <tr> <td>02 (50)</td> <td>2 3/4 (70)</td> <td>1 1/4 (32)</td> <td>4 3/4 (120)</td> </tr> <tr> <td>03 (75)</td> <td>2 3/4 (70)</td> <td>2 1/4 (57)</td> <td>4 3/4 (120)</td> </tr> <tr> <td>04 (100)</td> <td>3 1/4 (83)</td> <td>3 1/4 (83)</td> <td>6 (150)</td> </tr> </table>									A SIZE	02 (50)	03 (75)	04 (100)	B	4 (100) for Caulk, NO-HUB and Speedi-Set® 3 (76) for Threaded			A	B	C	D	02 (50)	2 3/4 (70)	1 1/4 (32)	4 3/4 (120)	03 (75)	2 3/4 (70)	2 1/4 (57)	4 3/4 (120)	04 (100)	3 1/4 (83)	3 1/4 (83)	6 (150)																	
A SIZE	02 (50)	03 (75)	04 (100)																																															
B	4 (100) for Caulk, NO-HUB and Speedi-Set® 3 (76) for Threaded																																																	
A	B	C	D																																															
02 (50)	2 3/4 (70)	1 1/4 (32)	4 3/4 (120)																																															
03 (75)	2 3/4 (70)	2 1/4 (57)	4 3/4 (120)																																															
04 (100)	3 1/4 (83)	3 1/4 (83)	6 (150)																																															
NOTE: Dimensions shown in parentheses are in millimeters. **Min 6 3/4 (170) hole required for core drilled application <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <th rowspan="2">Strainer Size</th> <th colspan="2">Collar In High Position</th> <th colspan="2">Collar In Low Position</th> <th colspan="2">Free Area SQ IN (SQ CM)</th> </tr> <tr> <th>DIA or SQ</th> <th>MIN</th> <th>MAX</th> <th>MIN</th> <th>MAX</th> <th>Round</th> <th>Square</th> </tr> <tr> <td>05 (125)</td> <td>1 1/4 (32)</td> <td>2 1/4 (57)</td> <td>3/4 (19)</td> <td>1 5/8 (41)</td> <td>7 (45)</td> <td>6.5 (42)</td> </tr> <tr> <td>06 (150)</td> <td>1 1/4 (32)</td> <td>2 1/4 (57)</td> <td>3/4 (19)</td> <td>1 5/8 (41)</td> <td>9 (58)</td> <td>12.5 (81)</td> </tr> <tr> <td>07 (180)</td> <td>1 1/4 (32)</td> <td>2 1/4 (57)</td> <td>7/8 (22)</td> <td>1 7/8 (48)</td> <td>14 (90)</td> <td>11 (71)</td> </tr> <tr> <td>08 (205)</td> <td>1 1/2 (38)</td> <td>2 1/2 (64)</td> <td>1 (25)</td> <td>1 7/8 (48)</td> <td>17 (110)</td> <td>14 (90)</td> </tr> </table>									Strainer Size	Collar In High Position		Collar In Low Position		Free Area SQ IN (SQ CM)		DIA or SQ	MIN	MAX	MIN	MAX	Round	Square	05 (125)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	7 (45)	6.5 (42)	06 (150)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	9 (58)	12.5 (81)	07 (180)	1 1/4 (32)	2 1/4 (57)	7/8 (22)	1 7/8 (48)	14 (90)	11 (71)	08 (205)	1 1/2 (38)	2 1/2 (64)	1 (25)	1 7/8 (48)	17 (110)	14 (90)
Strainer Size	Collar In High Position		Collar In Low Position		Free Area SQ IN (SQ CM)																																													
	DIA or SQ	MIN	MAX	MIN	MAX	Round	Square																																											
05 (125)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	7 (45)	6.5 (42)																																												
06 (150)	1 1/4 (32)	2 1/4 (57)	3/4 (19)	1 5/8 (41)	9 (58)	12.5 (81)																																												
07 (180)	1 1/4 (32)	2 1/4 (57)	7/8 (22)	1 7/8 (48)	14 (90)	11 (71)																																												
08 (205)	1 1/2 (38)	2 1/2 (64)	1 (25)	1 7/8 (48)	17 (110)	14 (90)																																												
REGULARLY FURNISHED: Duco Cast Iron Body and Flashing Collar with Adjustable Strainer Head with Secured Square Hole Grate and Funnel attached to the grate with concealed screws, permitting funnel to be moved to different positions on the grate. Type of Body and Strainer Head as indicated by Figure Number and Strainer Suffix Letter Selected. SEE PM 2789 FOR OPTIONAL STRAINER HEADS VARIATIONS: BODY: ☐ L Speedi-Set® Service Weight (Fig. 3510 only) ☐ LXH Speedi-Set® Extra Heavy (Fig. 3510 only) ☐ Trap Primer Connection -P05 (1/2") -P075 (3/4") STRAINER HEAD: ☐ Backwater Valve -V ☐ Ball Float Backwater Valve -BFV ☐ Sediment Bucket -B ☐ Vandal Proof Grate -U ☐ 6" (150) Dia. Funnel (Fig. 3581) ☐ 6(160) x 2 1/2(64) x 1"(25) High Oval Funnel (Fig. 3590) OPTIONAL MATERIALS: ☐ Cast Bronze Body -BB ☐ Chrome Plated Strainer -CP (See Strainers) ☐ Galvanized Body -G ☐ Nickel Bronze Strainer -NB (See Strainers) ☐ Polished Bronze Strainer -PB (See Strainers)																																																		
NOTES: All strainer shanks have 3 3/4" (95) -12 Thd. Collar not reversible in 4" (100) size. * Deduct 1/2" (13) when collar is inverted. ♦ Add 1/4" (6) for 8" (205) strainer																																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%;">H G F E</td> <td style="width: 10%;">4-19-24 7-26-23 3-13-23 4-17-96</td> <td style="width: 20%;">Added ASME Note Removed Function Added ® to Speedi-Set Added TPC</td> <td style="width: 10%;">HS HS KK CMD</td> <td style="width: 10%;">BW CL CL CL</td> <td style="width: 10%;">WEIGHT POUNDS</td> <td style="width: 10%;">VOLUME CUBIC FEET</td> <td style="width: 30%; text-align: center;"> FIGURE NUMBER 3510, 3515 </td> </tr> <tr> <td>REV.</td> <td>DATE</td> <td>DESCRIPTION</td> <td>BY</td> <td>CKD. BY</td> <td></td> <td></td> <td></td> </tr> </table>									H G F E	4-19-24 7-26-23 3-13-23 4-17-96	Added ASME Note Removed Function Added ® to Speedi-Set Added TPC	HS HS KK CMD	BW CL CL CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 3510, 3515	REV.	DATE	DESCRIPTION	BY	CKD. BY																													
H G F E	4-19-24 7-26-23 3-13-23 4-17-96	Added ASME Note Removed Function Added ® to Speedi-Set Added TPC	HS HS KK CMD	BW CL CL CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 3510, 3515																																											
REV.	DATE	DESCRIPTION	BY	CKD. BY																																														



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

D	 SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:				LOCATION 																																									
	OPTIONAL ADJUSTABLE STRAINER HEADS																																													
DRAWING NUMBER	PM2789 Pg 1 of 2					WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA																																								
SIZE	A																																													
SCALE:	NONE																																													
DATE:	9-19-85																																													
APPROVED BY:	SJM					DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE																																								
CHECKED BY:	J.D.																																													
DRAWN BY:	PJ																																													
FIGURE NUMBER	3510 SERIES OPTIONAL STRAINER HEADS																																													
ROUND TOP ROUND INTEGRAL FUNNEL (SUFFIX -F10) RECTANGULAR TOP ROUND FUNNEL (Suffix -F13, -F14, -F15, -F16, -F17 & -F18)																																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>*SUFFIX</th> <th>-F10</th> <th>-F13</th> <th>-F14</th> <th>-F15</th> <th>-F16</th> <th>-F17</th> <th>-F18</th> </tr> <tr> <td>B X B'</td> <td>-</td> <td>4 1/4 (110) x 8 (205)</td> <td>4 (100) x 12 (305)</td> <td>5 (125) x 9 (230)</td> <td>5 (125) x 13 (330)</td> <td>5 (125) x 17 (430)</td> <td>6 (150) x 10 (255)</td> </tr> <tr> <td>H</td> <td>2 3/8 (60)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> <td>2 1/4 (57)</td> <td>3 (76)</td> <td>3 (76)</td> <td>2 1/4 (57)</td> </tr> <tr> <td>X MIN</td> <td>1 1/2 (38)</td> <td>1 3/8 (35)</td> <td>1 7/8 (48)</td> <td>1 3/8 (35)</td> <td>2 1/8 (54)</td> <td>2 1/4 (57)</td> <td>1 3/8 (35)</td> </tr> <tr> <td>X MAX</td> <td>2 1/2 (64)</td> <td>2 1/4 (57)</td> <td>2 3/4 (70)</td> <td>2 3/8 (60)</td> <td>3 (76)</td> <td>3 1/8 (79)</td> <td>2 3/8 (79)</td> </tr> </table> *Specify Size, Type & Finish. eg: -F10-08CP							*SUFFIX	-F10	-F13	-F14	-F15	-F16	-F17	-F18	B X B'	-	4 1/4 (110) x 8 (205)	4 (100) x 12 (305)	5 (125) x 9 (230)	5 (125) x 13 (330)	5 (125) x 17 (430)	6 (150) x 10 (255)	H	2 3/8 (60)	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	3 (76)	3 (76)	2 1/4 (57)	X MIN	1 1/2 (38)	1 3/8 (35)	1 7/8 (48)	1 3/8 (35)	2 1/8 (54)	2 1/4 (57)	1 3/8 (35)	X MAX	2 1/2 (64)	2 1/4 (57)	2 3/4 (70)	2 3/8 (60)	3 (76)	3 1/8 (79)	2 3/8 (79)
*SUFFIX	-F10	-F13	-F14	-F15	-F16	-F17	-F18																																							
B X B'	-	4 1/4 (110) x 8 (205)	4 (100) x 12 (305)	5 (125) x 9 (230)	5 (125) x 13 (330)	5 (125) x 17 (430)	6 (150) x 10 (255)																																							
H	2 3/8 (60)	2 1/4 (57)	2 1/2 (64)	2 1/4 (57)	3 (76)	3 (76)	2 1/4 (57)																																							
X MIN	1 1/2 (38)	1 3/8 (35)	1 7/8 (48)	1 3/8 (35)	2 1/8 (54)	2 1/4 (57)	1 3/8 (35)																																							
X MAX	2 1/2 (64)	2 1/4 (57)	2 3/4 (70)	2 3/8 (60)	3 (76)	3 1/8 (79)	2 3/8 (79)																																							
ROUND TOP ROUND FUNNEL (SUFFIX -F11) SQUARE TOP ROUND FUNNEL (SUFFIX -F12)																																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>*SUFFIX</th> <th colspan="6">-F11 & -F12</th> </tr> <tr> <td>B DIA or SQ</td> <td>05 (125)</td> <td>06 (150)</td> <td>07 (180)</td> <td>08 (205)</td> <td>09 (230)</td> <td>10 (255)</td> </tr> <tr> <td>H</td> <td>2 (51)</td> <td>2 (51)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> <td>2 1/2 (64)</td> <td>2 3/4 (70)</td> </tr> <tr> <td>X MIN</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/2 (38)</td> <td>1 1/2 (38)</td> <td>1 1/2 (38)</td> </tr> <tr> <td>X MAX</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> <td>2 1/2 (64)</td> <td>2 3/8 (60)</td> </tr> </table> *Specify Size, Type & Finish. eg: -F11-06CP							*SUFFIX	-F11 & -F12						B DIA or SQ	05 (125)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)	H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)	X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)	X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/8 (60)					
*SUFFIX	-F11 & -F12																																													
B DIA or SQ	05 (125)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)																																								
H	2 (51)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)																																								
X MIN	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)																																								
X MAX	2 1/4 (57)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/8 (60)																																								
ROUND TOP OVAL INTEGRAL FUNNEL (SUFFIX -F19) ROUND TOP OVAL FUNNEL (Suffix -F20, -F21, -F22, -F23 & -F24)																																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>*SUFFIX</th> <th>-F19</th> <th>-F20</th> <th>-F21</th> <th>-F22</th> <th>-F23</th> <th>-F24</th> </tr> <tr> <td>B DIA</td> <td>08 (205)</td> <td>06 (150)</td> <td>07 (180)</td> <td>08 (205)</td> <td>09 (230)</td> <td>10 (255)</td> </tr> <tr> <td>H</td> <td>2 1/2 (64)</td> <td>2 (51)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> <td>2 1/2 (64)</td> <td>2 3/4 (70)</td> </tr> <tr> <td>X MIN</td> <td>1 1/2 (38)</td> <td>1 1/4 (32)</td> <td>1 1/4 (32)</td> <td>1 1/2 (38)</td> <td>1 1/2 (38)</td> <td>1 1/2 (38)</td> </tr> <tr> <td>X MAX</td> <td>2 1/2 (64)</td> <td>2 1/4 (57)</td> <td>2 1/4 (57)</td> <td>2 1/2 (64)</td> <td>2 1/2 (64)</td> <td>2 3/4 (70)</td> </tr> </table> *Specify Size, Type & Finish. eg: -F19CP							*SUFFIX	-F19	-F20	-F21	-F22	-F23	-F24	B DIA	08 (205)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)	H	2 1/2 (64)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)	X MIN	1 1/2 (38)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)	X MAX	2 1/2 (64)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)					
*SUFFIX	-F19	-F20	-F21	-F22	-F23	-F24																																								
B DIA	08 (205)	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)																																								
H	2 1/2 (64)	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)																																								
X MIN	1 1/2 (38)	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)	1 1/2 (38)																																								
X MAX	2 1/2 (64)	2 1/4 (57)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30px;">D</td> <td style="width: 100px;">7-31-08</td> <td style="width: 200px;">Revised Dim</td> <td style="width: 50px;">TBW</td> <td style="width: 50px;">CL</td> <td rowspan="3" style="width: 100px;">WEIGHT POUNDS</td> <td rowspan="3" style="width: 100px;">VOLUME CUBIC FEET</td> <td rowspan="3" style="width: 150px; text-align: center;"> FIGURE NUMBER 3510 SERIES OPTIONAL STRAINER HEADS </td> </tr> <tr> <td>C</td> <td>11-2-95</td> <td>Revised</td> <td>EMB</td> <td>BS</td> </tr> <tr> <td>B</td> <td>7-27-95</td> <td>Added Millimeters & Made 2 Pgs</td> <td>EMB</td> <td>BS</td> </tr> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>REV.</td> <td>DATE</td> <td>DESCRIPTION</td> <td>BY</td> <td>CKD. BY</td> </tr> </table>							D	7-31-08	Revised Dim	TBW	CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 3510 SERIES OPTIONAL STRAINER HEADS	C	11-2-95	Revised	EMB	BS	B	7-27-95	Added Millimeters & Made 2 Pgs	EMB	BS	REV.	DATE	DESCRIPTION	BY	CKD. BY																	
D	7-31-08	Revised Dim	TBW	CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 3510 SERIES OPTIONAL STRAINER HEADS																																							
C	11-2-95	Revised	EMB	BS																																										
B	7-27-95	Added Millimeters & Made 2 Pgs	EMB	BS																																										
REV.	DATE	DESCRIPTION	BY	CKD. BY																																										

C

DRAWING NUMBER
PM2789 Pg 2

SIZE
A

SCALE:
NONE

DATE:
9-19-85

APPROVED BY:
SJM

CHECKED BY:
J.D.

DRAWN BY:
PJ

3510 SERIES OPTIONAL
STRAINER HEADS

FIGURE
NUMBER

SMITH®



JAY R. SMITH MFG. CO.®

MEMBER OF MORRIS GROUP INTERNATIONAL

POST OFFICE BOX 3237

MONTGOMERY, ALABAMA 36109-0237 (USA)

TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com



PLUMBING AND DRAINAGE

INSTITUTE



AMERICAN PLUMBING

DRAINAGE

INSTITUTE

MEMBER OF:



LOCATION

8 1/4 x 3 1/4
(210) x (83)

4 1/2 (115)

H

B SQ

SQUARE TOP
OVAL FUNNEL

8 1/4 x 3 1/4
(210) x (83)

4 1/2 (115)

H

B x B'

RECTANGULAR TOP
OVAL FUNNEL

*SUFFIX	-F25	-F26	-F27	-F28	-F29
B SQ	06 (150)	07 (180)	08 (205)	09 (230)	10 (255)
H	2 (51)	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)
X	MIN	1 1/4 (32)	1 1/4 (32)	1 1/2 (38)	1 1/2 (38)
	MAX	2 1/4 (57)	2 1/2 (64)	2 1/2 (64)	2 3/4 (70)

*SUFFIX	-F30	-F31	-F32	-F33	-F34	-F35
B x B'	4 1/4 X 8 (110) X (205)	4 x 12 (100) x (305)	5 x 9 (125) x (230)	5 x 13 (125) x (330)	6 x 10 (150) x (255)	5 x 17 (125) x (430)
H	2 1/2 (57)	2 1/2 (64)	2 1/4 (57)	3 (76)	2 1/4 (57)	3 (76)
X	MIN	1 3/8 (35)	1 7/8 (48)	1 3/8 (35)	1 3/8 (35)	2 1/4 (57)
	MAX	2 3/8 (60)	2 3/4 (70)	2 3/8 (60)	3 (76)	2 3/8 (60)

B DIA

H

ROUND TOP
ANTI-SPLASH RIM

Anti-splash rim permits a flush
with floor funnel installation.

*SUFFIX	-F37	-F38
B DIA	7 (180)	9 (230)
H	3 1/4 (83)	3 1/2 (89)
X	MIN	2 5/8 (67)
	MAX	3 1/2 (89)

A

6"(150) Reg. or
as Specified

2 (51)

INDIRECT WASTE
STANDPIPE

Standpipe design permits extension of
standpipe height as required and can
also serve as an overflow.

*SUFFIX	-F40	-F41
A SIZE	2 (51)	3 (76)
X	MIN	3/4 (19)
	MAX	2 1/8 (54)

*Specify Size, Type & Finish. eg: -F40NB or -F41CP

FUNNEL ASSEMBLIES ONLY

4 DIA
(100)

4 1/4 (110)

2 1/2
(64)

Fig. 3580

4(100)
DIA

4 1/4 (110)

Grate As Specified

2
(51)

(2) 10-24
Securing Screw
and Washers

Fig. 3580

6 x 2 1/2 Oval
(150) x (64)

1 (25)

5 x 2 1/2
(125) x (64)

Fig. 3590

6 DIA (150)

4 1/4 (110)

2 1/2
(64)

Fig. 3581

8 1/4 x 3 1/4 Oval
(210) x (83)

4 1/2 (115)

5 x 2 1/2
(125) x (64)

Fig. 3591

OPTIONAL MATERIALS:

☐

 Acid Resistant Coated Cast Iron -ARC

☐

 Chrome Plated -CP

☐

 Duco Cast Iron -CI

☐

 Galvanized Cast Iron -G

☐

 Nickel Bronze -NB

☐

 Polished Bronze -PB

☐

 Rough Bronze -RB

☐

 Stainless Steel (See Fig. 9703 and 9704)

C	7-31-08	Revised Dim & Table Added MM's & Made 2 Pgs Submittal Update	TBW	CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 3510 SERIES OPTIONAL STRAINER HEADS
B	7-27-95		EMB	BS			
A	1-30-95		CMB	BS			
REV.	DATE	DESCRIPTION	BY	CKD. BY			



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov