

N	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:				LOCATION
	TERRAZZO FLOOR CLEANOUTS WITH "TWIS-TO-FLOOR®" ADJUSTABLE TOPS SQUARE NICKEL BRONZE TOP WITH TERRAZZO RECESS				
	DRAWING NUMBER	S4200			
	SIZE	A			
SCALE:	NONE				
DATE:	2-16-70				
APPROVED BY:	JM				
CHECKED BY:	BH				
DRAWN BY:	RK				
FIGURE NUMBER	4200 SERIES				

Secured Cover

6"(150) SQ.

Adj. Top and Frame

Min. 3 3/16"(81)
Max. 4 3/8"(111)

Flashing Clamp (when specified)

Flashing Flange (when specified)

3 1/2"(89)
Plug Size

4"(100)

2 3/16"(56)

A

9"(230) Dia.

TWIS-TO-FLOOR® ADJUSTMENT

NO-HUB OUTLET

"A" (Pipe Size) = 02(50), 03(75), 04(100) or 05(125)

Conforms to ASME A112.36.2/CSA B79.2

□	Fig. 4200S.....Gasket Seal - ABS Plug
□	Fig. 4201S.....Gasket Seal - Bronze Plug
□	Fig. 4203S.....Taper Thread - Bronze Plug
□	Fig. 4204S.....Taper Thread - ABS Plug

(Twis-to-Floor® design shown with gasketed plug.)

NOTE: Dimensions shown in parentheses are in millimeters.

REGULARLY FURNISHED:

Duco Cast Iron Cleanout with Square Adjustable Secured Nickel Bronze Top with 1/2"(13) Terrazzo Recess. Closure Plug Type as Indicated By Figure Number Selected.

VARIATIONS:

□	Flashing Flange -F
□	Flange with Flashing Clamp -F-C
□	Vandal Proof Top -U

OPTIONAL MATERIALS:

□	Galvanized Cast Iron -G
□	Polished Bronze Top -PB

N	4-11-24	Added ASME Note	HS	CL	WEIGHT	VOLUME	FIGURE NUMBER
M	8-17-23	Removed Function	HS	CL	POUNDS	CUBIC FEET	4200 SERIES
L	1-20-22	Removed "C.O." cast in"	KK	CL			
K	07/29/02	Corrected Clamp & Flange view	JJ	CL			
REV.	DATE	DESCRIPTION	BY	CKD. BY			



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

B	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF:				LOCATION
	TERRAZZO FLOOR CLEANOUTS WITH "TWIS-TO-FLOOR®" ADJUSTABLE TOPS				
DRAWING NUMBER	S4200BS				
SIZE	A				
SCALE:	NONE				
DATE:	5-5-06				
APPROVED BY:	CEL				
CHECKED BY:	CL				
DRAWN BY:	RN				
FIGURE NUMBER	4203				

SQUARE NICKEL BRONZE TOP WITH TERRAZZO RECESS

SPIGOT OUTLET▲
"A" (Pipe Size) = 06(150) & 08(200)

Conforms to ASME A112.36.2/CSA B79.2

"TWIS-TO-FLOOR®" ADJUSTMENT

SPIGOT OUTLET ▲

☐ Fig. 4203S.....Taper Thread - Bronze Plug

▲ Sized for Service Weight and/or NO-HUB.

* When Flange-F is specified Min. 1 1/2 (38) becomes 2 (51)

REGULARLY FURNISHED:

Duct Cast Iron Cleanout with Taper Thread Bronze Plug and Square Adjustable Secured Nickel Bronze Top with 1/2 (13) Terrazzo Recess.

VARIATIONS:

☐ Flashing Flange -F

☐ Flange with Flashing Clamp -F-C

☐ Vandal Proof Top -U

OPTIONAL MATERIALS:

☐ Galvanized Cast Iron -G

☐ Polished Bronze Top -PB

NOTE: Dimensions shown in parentheses are in millimeters.

REV.	DATE	DESCRIPTION	BY	CKD. BY	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER
B A	4-11-24 8-17-23	Added ASME Note Removed Function	HS HS	CL CL			4203



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov