

R	JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF:				LOCATION 	
	FLOOR CLEANOUTS WITH "TWIS-TO-FLOOR®" ADJUSTABLE TOPS FOR UNFINISHED AREAS					
	ROUND EXTRA HEAVY DUTY CAST IRON TOP					
	TWIS-TO-FLOOR® ADJUSTMENT NO-HUB OUTLET "A" (Pipe Size) = 02(50), 03(75) or 04(100) Conforms to ASME A112.36.2/CSA B79.2					
REGULARLY FURNISHED: Duco Cast Iron Cleanout with Round Adjustable Scoriated Secured Cast Iron Top. Closure Plug Type as Indicated by Figure Number Selected. VARIATIONS: ☐ Fig. 4220S.....Gasket Seal - ABS Plug ☐ Fig. 4221S.....Gasket Seal - Bronze Plug ☐ Fig. 4223S.....Taper Thread - Bronze Plug ☐ Fig. 4224S.....Taper Thread - ABS Plug ☐ Flashing Flange -F ☐ Flange with Flashing Clamp -F-C ☐ Vandal Proof Top -U (Twis-to-Floor® design shown with gasketed plug.) NOTE: Dimensions shown in parentheses are in millimeters.						

REGULARLY FURNISHED:
 Duco Cast Iron Cleanout with Round Adjustable Scoriated Secured Cast Iron Top. Closure Plug Type as Indicated by Figure Number Selected.

VARIATIONS:

☐ Fig. 4220S.....Gasket Seal - ABS Plug
☐ Fig. 4221S.....Gasket Seal - Bronze Plug
☐ Fig. 4223S.....Taper Thread - Bronze Plug
☐ Fig. 4224S.....Taper Thread - ABS Plug

☐ Flashing Flange -F
☐ Flange with Flashing Clamp -F-C
☐ Vandal Proof Top -U

OPTIONAL MATERIALS:

☐ Galvanized Cast Iron -G
☐ Ductile Iron Cover -M

C	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:				LOCATION 												
	FLOOR CLEANOUTS WITH "TWIS-TO-FLOOR®" ADJUSTABLE TOPS FOR UNFINISHED AREAS																
4223	DRAWING NUMBER S4220BS		SIZE A			SCALE: NONE		DATE: 5-5-06		APPROVED BY: CEL		CHECKED BY: CL		DRAWN BY: RN			
	ROUND HEAVY DUTY CAST IRON TOP																
	SPIGOT OUTLET▲ "A" (Pipe Size) = 06(150) & 08(200)																
	Conforms to ASME A112.36.2/CSA B79.2																
	"TWIS-TO-FLOOR®" ADJUSTMENT SPIGOT OUTLET▲ ☐ Fig. 4223S.....Taper Thread - Bronze Plug																
	REGULARLY FURNISHED: Ducto Cast Iron Cleanout with Taper Thread Bronze Plug and Round Adjustable Scoriated Secured Cast Iron Top.																
	VARIATIONS: ☐ Flashing Flange -F ☐ Flange with Flashing Clamp -F-C ☐ Vandal Proof Top -U																
	OPTIONAL MATERIALS: ☐ Galvanized Cast Iron -G ☐ Ductile Iron Cover-M (Extra Heavy Duty)																
	NOTE: Dimensions shown in parentheses are in millimeters.																
FIGURE NUMBER		REV.		DATE		DESCRIPTION		BY		CKD. BY		WEIGHT POUNDS		VOLUME CUBIC FEET		FIGURE NUMBER 4223	



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov