

J	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:					LOCATION																																																														
	CAULK FERRULE CLEANOUTS WITH FRAME AND COVER																																																																			
	TAPER THREAD PLUG WITH FRAME AND SCORIATED COVER																																																																			
	Anchor Lugs "C.O." Cast in Secured Cover Scoriated Nickel Bronze Cover and Frame Anchor Lugs Scoriated Nickel Bronze Cover and Frame Secured Cover ☐ FIG. 4440CFACE-OF-WALL COVER ☐ FIG. 4441CFLUSH-WITH-WALL COVER																																																																			
<table border="1" style="width: 100%; border-collapse: collapse; font-size: 0.8em;"> <thead> <tr> <th rowspan="2"></th> <th rowspan="2">A SIZE</th> <th colspan="2">B OPENING</th> <th rowspan="2">C SIZE</th> <th rowspan="2">D</th> <th rowspan="2">E DIA</th> <th rowspan="2">F SQ</th> <th rowspan="2">G SQ</th> </tr> <tr> <th>DIA</th> <th>SQ</th> </tr> </thead> <tbody> <tr> <td>▲ 02 (50)</td> <td>4 (100)</td> <td>6 x 6 (150) x (150)</td> <td>1 1/2 (38)</td> <td>3 1/2 (89)</td> <td>4 1/2 (115)</td> <td>7 (180)</td> <td>5 1/2 (140)</td> </tr> <tr> <td>▲ 03 (80)</td> <td>5 1/2 (140)</td> <td>6 x 6 (150) x (150)</td> <td>2 1/2 (64)</td> <td>3 3/4 (95)</td> <td>5 3/4 (145)</td> <td>7 (180)</td> <td>5 1/2 (140)</td> </tr> <tr> <td>▲ 04 (100)</td> <td>6 (150)</td> <td>6 x 6 (150) x (150)</td> <td>3 1/2 (89)</td> <td>4 1/4 (110)</td> <td>6 1/2 (165)</td> <td>7 (180)</td> <td>5 1/2 (140)</td> </tr> <tr> <td>05 (125)</td> <td>6 (150)</td> <td>8 x 8 (205) x (205)</td> <td>4 1/2 (115)</td> <td>4 1/4 (110)</td> <td>6 1/2 (165)</td> <td>9 (230)</td> <td>7 1/2 (190)</td> </tr> <tr> <td>06 (150)</td> <td>8 (205)</td> <td>8 x 8 (205) x (205)</td> <td>5 1/2 (140)</td> <td>4 1/4 (110)</td> <td>8 1/2 (215)</td> <td>9 (230)</td> <td>7 1/2 (190)</td> </tr> <tr> <td>08 (200)</td> <td>10 (255)</td> <td>10 x 10 (255) x (255)</td> <td>7 1/2 (190)</td> <td>4 1/2 (115)</td> <td>10 1/2 (265)</td> <td>11 (280)</td> <td>9 1/2 (240)</td> </tr> </tbody> </table>											A SIZE	B OPENING		C SIZE	D	E DIA	F SQ	G SQ	DIA	SQ	▲ 02 (50)	4 (100)	6 x 6 (150) x (150)	1 1/2 (38)	3 1/2 (89)	4 1/2 (115)	7 (180)	5 1/2 (140)	▲ 03 (80)	5 1/2 (140)	6 x 6 (150) x (150)	2 1/2 (64)	3 3/4 (95)	5 3/4 (145)	7 (180)	5 1/2 (140)	▲ 04 (100)	6 (150)	6 x 6 (150) x (150)	3 1/2 (89)	4 1/4 (110)	6 1/2 (165)	7 (180)	5 1/2 (140)	05 (125)	6 (150)	8 x 8 (205) x (205)	4 1/2 (115)	4 1/4 (110)	6 1/2 (165)	9 (230)	7 1/2 (190)	06 (150)	8 (205)	8 x 8 (205) x (205)	5 1/2 (140)	4 1/4 (110)	8 1/2 (215)	9 (230)	7 1/2 (190)	08 (200)	10 (255)	10 x 10 (255) x (255)	7 1/2 (190)	4 1/2 (115)	10 1/2 (265)	11 (280)	9 1/2 (240)
	A SIZE	B OPENING		C SIZE	D	E DIA	F SQ	G SQ																																																												
		DIA	SQ																																																																	
▲ 02 (50)	4 (100)	6 x 6 (150) x (150)	1 1/2 (38)	3 1/2 (89)	4 1/2 (115)	7 (180)	5 1/2 (140)																																																													
▲ 03 (80)	5 1/2 (140)	6 x 6 (150) x (150)	2 1/2 (64)	3 3/4 (95)	5 3/4 (145)	7 (180)	5 1/2 (140)																																																													
▲ 04 (100)	6 (150)	6 x 6 (150) x (150)	3 1/2 (89)	4 1/4 (110)	6 1/2 (165)	7 (180)	5 1/2 (140)																																																													
05 (125)	6 (150)	8 x 8 (205) x (205)	4 1/2 (115)	4 1/4 (110)	6 1/2 (165)	9 (230)	7 1/2 (190)																																																													
06 (150)	8 (205)	8 x 8 (205) x (205)	5 1/2 (140)	4 1/4 (110)	8 1/2 (215)	9 (230)	7 1/2 (190)																																																													
08 (200)	10 (255)	10 x 10 (255) x (255)	7 1/2 (190)	4 1/2 (115)	10 1/2 (265)	11 (280)	9 1/2 (240)																																																													
▲ Sized for Service Weight and/or NO-HUB NOTE: Dimensions shown in parentheses are in millimeters.																																																																				
REGULARLY FURNISHED: Duco Cast Iron Caulk Ferrule with Cast Bronze Taper Thread Plug and Secured Scoriated Nickel Bronze Cover and Frame with Anchor Lugs. Type of Cover as Indicated by Figure Number Selected. VARIATIONS: ☐ Cover Drilled in Center and Furnished with 1/4"(6)-20 x 2 1/2"(64) Long Screw ☐ Smooth Cover -SC ☐ "T" Handle Plug -TH ☐ Plug Tapped 1/4"(6) -20 Thread ☐ Vandal Proof Screws -U OPTIONAL MATERIALS: ☐ Cast Bronze Body -BB ☐ Polished Bronze Frame and Cover -PB																																																																				
FIGURE NUMBER	J H F		8-18-23 10-7-14 10-3-13 10-20-98		Removed Function Revised Variations Revised Function Revised S.W. and/or N.H		HS TBW TBW TBW		CL BW SJM JCS		WEIGHT POUNDS		VOLUME CUBIC FEET		FIGURE NUMBER 4440, 4441																																																					
	REV.		DATE		DESCRIPTION		BY		CKD. BY																																																											



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov