

H	JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF:					LOCATION 				
	HOSE VALVES									
FIGURE NUMBER 5670	DRAWING NUMBER s5670	SIZE A	SCALE: NONE	DATE: 01/11/11	APPROVED BY: CL	CHECKED BY: CL	DRAWN BY: JJ	DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE		
	BENT NOSE WITH FLANGE									
 Fig. 5670 (Less Vacuum Breaker) Fig. 5670 -H (With ASSE 1011 Vacuum Breaker)										
NOTES: - The AB100, AB1953, California Lead Law, and NSF/ANSI Standard 61 - Drinking Water Components are not applicable to Jay R. Smith hydrants as they do not convey/dispense water for human consumption through drinking or cooking. - Dimensions shown in parentheses are in millimeters. FOR IRRIGATION PURPOSES ONLY. - Temperature Range: 33.0°F to 140.0°F (0.6°C to 60.0°C).										
REGULARLY FURNISHED: Hose Valves have a Rough Finish Brass Body with Machined Brass Vandal-Resistant Lock Shield Bonnet, Removable Wheel Handle, 3/4"(19) NPT Female Threaded Inlet and 3/4"(19) Hose Connection. OPTIONAL MATERIALS: Polished Chrome Plated -CP Rough Chrome Plated -CR										
Installer is responsible for providing a 100% watertight positive seal at the hydrant to wall interface. Seal all the flange with an appropriate sealant recommended by a sealant manufacturer. NOTE: Jay R. Smith does not warrant the performance or life expectancy of the sealant material.										
NOTE: Dimensions shown in Parentheses are in millimeters.										
H G F E 2-3-25 4-23-24 8-4-23 3-22-23 REV. DATE Revised Notes Revised Fig. Description Removed Function Revised Note 1 DESCRIPTION HS HS HS KK BW CL CL JT BY CKD. BY WEIGHT POUNDS VOLUME CUBIC FEET FIGURE NUMBER										
5670										



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov