

D	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:					LOCATION
	BACKWATER VALVES					
	DRAIN OUTLET VALVES					
A (Pipe Size) = 02(50), 03(75), 04(100), 05(125) or 06(150) Sized for Service Weight and/or NO-HUB ☐ Fig. 7080S . . . SPIGOT OUTLET ☐ Fig. 7082T . . . THREADED OUTLET REGULARLY FURNISHED: Duco Cast Iron Body with Ball Float Backwater Valve. OPTIONAL MATERIALS: ☐ Bronze Body -BB ☐ Galvanized Cast Iron -G NOTE: These valves offer protection against backwater surges. Backflow is prevented when valve is not obstructed by debris or sludge. Use for gravity flow only, not for pressurized applications. NOTE: Dimensions shown in parentheses are in millimeters.						
7080	D C B A 7-20-23 7-10-95 8-18-94 10-90 Removed Function Added Millimeters Submittal Update Added note HS EMB EMB TBW CL BS BS McD WEIGHT POUNDS VOLUME CUBIC FEET FIGURE NUMBER 7080					
	REV.	DATE	DESCRIPTION	BY	CKD. BY	



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov