

Q						LOCATION																																																																																																																																																											
	GREASE INTERCEPTORS																																																																																																																																																																
	GREASE INTERCEPTORS WITH SEMI-AUTOMATIC DRAW-OFF																																																																																																																																																																
DRAWING NUMBER	SIZE		SCALE:	DATE:	APPROVED BY:	CHECKED BY:	DRAWN BY:																																																																																																																																																										
S8000GT	A		NONE	04-24-85	TD	TD	PJ																																																																																																																																																										
WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA																																																																																																																																																																	
DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE																																																																																																																																																																	
<table border="1" style="width:100%; border-collapse: collapse; font-size: 10px;"> <thead> <tr> <th rowspan="3">Fig. #</th> <th rowspan="3">GPM Flow Rate</th> <th rowspan="3">Grease Cap Lbs.</th> <th rowspan="3">Inlet and Outlet Size *A</th> <th colspan="6">Dimensions</th> <th rowspan="3">C.O. Plug Size</th> <th rowspan="3">Line Shut-off Valve</th> </tr> <tr> <th colspan="3">Roughing Dimensions</th> <th colspan="2">Body</th> </tr> <tr> <th>B</th> <th>C</th> <th>D</th> <th>Height E</th> <th>Width F</th> </tr> </thead> <tbody> <tr><td>8007GT</td><td>07</td><td>14</td><td>02 (50)</td><td>8 1/2 (215)</td><td>3 1/2 (89)</td><td>19 (485)</td><td>12 (305)</td><td>10 3/4 (275)</td><td>2 (51)</td><td>6 3/4 (175)</td></tr> <tr><td>8010GT</td><td>10</td><td>20</td><td>02 (50)</td><td>9 1/2 (240)</td><td>3 3/4 (95)</td><td>21 1/4 (540)</td><td>13 1/4 (335)</td><td>13 (330)</td><td>2 (51)</td><td>6 3/4 (175)</td></tr> <tr><td>8015GT</td><td>15</td><td>30</td><td>02 (50)</td><td>12 (305)</td><td>3 1/2 (89)</td><td>25 (635)</td><td>15 1/2 (395)</td><td>14 (355)</td><td>2 (51)</td><td>6 3/4 (175)</td></tr> <tr><td>8020GT</td><td>20</td><td>40</td><td>03 (75)</td><td>13 (330)</td><td>4 (100)</td><td>28 1/2 (725)</td><td>17 (430)</td><td>15 3/4 (400)</td><td>2 (51)</td><td>10 (255)</td></tr> <tr><td>8025GT</td><td>25</td><td>50</td><td>03 (75)</td><td>15 1/4 (390)</td><td>4 1/2 (115)</td><td>30 (760)</td><td>19 3/4 (500)</td><td>16 3/4 (425)</td><td>2 (51)</td><td>10 (255)</td></tr> <tr><td>8035GT</td><td>35</td><td>70</td><td>03 (75)</td><td>16 (405)</td><td>5 (125)</td><td>32 1/2 (825)</td><td>21 (535)</td><td>18 1/4 (465)</td><td>2 (51)</td><td>10 (255)</td></tr> <tr><td>8050GT</td><td>50</td><td>100</td><td>03 (75)</td><td>17 1/2 (445)</td><td>6 3/4 (170)</td><td>35 1/2 (900)</td><td>24 1/4 (615)</td><td>20 3/4 (525)</td><td>2 (51)</td><td>10 (255)</td></tr> <tr><td>8075GT</td><td>75</td><td>150</td><td>04 (100)</td><td>21 1/2 (545)</td><td>15 1/2 (395)</td><td>50 (1270)</td><td>37 (940)</td><td>30 1/2 (775)</td><td>3 (76)</td><td>12 3/4 (325)</td></tr> <tr><td colspan="11" style="text-align: center; font-weight: bold;">LOW TYPE</td></tr> <tr><td>8120GT</td><td>20</td><td>40</td><td>03 (75)</td><td>7 (180)</td><td>3 1/2 (89)</td><td>38 1/2 (980)</td><td>10 1/2 (265)</td><td>21 3/4 (550)</td><td>2 (51)</td><td>10 (255)</td></tr> <tr><td>8135GT</td><td>35</td><td>70</td><td>03 (75)</td><td>7 (180)</td><td>4 3/4 (120)</td><td>49 1/2 (1257)</td><td>11 3/4 (300)</td><td>27 3/4 (705)</td><td>2 (51)</td><td>10 (255)</td></tr> <tr><td>8150GT</td><td>50</td><td>100</td><td>03 (75)</td><td>10 (255)</td><td>6 (150)</td><td>49 1/2 (1257)</td><td>16 (405)</td><td>27 3/4 (705)</td><td>2 (51)</td><td>10 (255)</td></tr> </tbody> </table>								Fig. #	GPM Flow Rate	Grease Cap Lbs.	Inlet and Outlet Size *A	Dimensions						C.O. Plug Size	Line Shut-off Valve	Roughing Dimensions			Body		B	C	D	Height E	Width F	8007GT	07	14	02 (50)	8 1/2 (215)	3 1/2 (89)	19 (485)	12 (305)	10 3/4 (275)	2 (51)	6 3/4 (175)	8010GT	10	20	02 (50)	9 1/2 (240)	3 3/4 (95)	21 1/4 (540)	13 1/4 (335)	13 (330)	2 (51)	6 3/4 (175)	8015GT	15	30	02 (50)	12 (305)	3 1/2 (89)	25 (635)	15 1/2 (395)	14 (355)	2 (51)	6 3/4 (175)	8020GT	20	40	03 (75)	13 (330)	4 (100)	28 1/2 (725)	17 (430)	15 3/4 (400)	2 (51)	10 (255)	8025GT	25	50	03 (75)	15 1/4 (390)	4 1/2 (115)	30 (760)	19 3/4 (500)	16 3/4 (425)	2 (51)	10 (255)	8035GT	35	70	03 (75)	16 (405)	5 (125)	32 1/2 (825)	21 (535)	18 1/4 (465)	2 (51)	10 (255)	8050GT	50	100	03 (75)	17 1/2 (445)	6 3/4 (170)	35 1/2 (900)	24 1/4 (615)	20 3/4 (525)	2 (51)	10 (255)	8075GT	75	150	04 (100)	21 1/2 (545)	15 1/2 (395)	50 (1270)	37 (940)	30 1/2 (775)	3 (76)	12 3/4 (325)	LOW TYPE											8120GT	20	40	03 (75)	7 (180)	3 1/2 (89)	38 1/2 (980)	10 1/2 (265)	21 3/4 (550)	2 (51)	10 (255)	8135GT	35	70	03 (75)	7 (180)	4 3/4 (120)	49 1/2 (1257)	11 3/4 (300)	27 3/4 (705)	2 (51)	10 (255)	8150GT	50	100	03 (75)	10 (255)	6 (150)	49 1/2 (1257)	16 (405)	27 3/4 (705)	2 (51)	10 (255)
Fig. #	GPM Flow Rate	Grease Cap Lbs.	Inlet and Outlet Size *A	Dimensions								C.O. Plug Size	Line Shut-off Valve																																																																																																																																																				
				Roughing Dimensions			Body																																																																																																																																																										
				B	C	D	Height E	Width F																																																																																																																																																									
8007GT	07	14	02 (50)	8 1/2 (215)	3 1/2 (89)	19 (485)	12 (305)	10 3/4 (275)	2 (51)	6 3/4 (175)																																																																																																																																																							
8010GT	10	20	02 (50)	9 1/2 (240)	3 3/4 (95)	21 1/4 (540)	13 1/4 (335)	13 (330)	2 (51)	6 3/4 (175)																																																																																																																																																							
8015GT	15	30	02 (50)	12 (305)	3 1/2 (89)	25 (635)	15 1/2 (395)	14 (355)	2 (51)	6 3/4 (175)																																																																																																																																																							
8020GT	20	40	03 (75)	13 (330)	4 (100)	28 1/2 (725)	17 (430)	15 3/4 (400)	2 (51)	10 (255)																																																																																																																																																							
8025GT	25	50	03 (75)	15 1/4 (390)	4 1/2 (115)	30 (760)	19 3/4 (500)	16 3/4 (425)	2 (51)	10 (255)																																																																																																																																																							
8035GT	35	70	03 (75)	16 (405)	5 (125)	32 1/2 (825)	21 (535)	18 1/4 (465)	2 (51)	10 (255)																																																																																																																																																							
8050GT	50	100	03 (75)	17 1/2 (445)	6 3/4 (170)	35 1/2 (900)	24 1/4 (615)	20 3/4 (525)	2 (51)	10 (255)																																																																																																																																																							
8075GT	75	150	04 (100)	21 1/2 (545)	15 1/2 (395)	50 (1270)	37 (940)	30 1/2 (775)	3 (76)	12 3/4 (325)																																																																																																																																																							
LOW TYPE																																																																																																																																																																	
8120GT	20	40	03 (75)	7 (180)	3 1/2 (89)	38 1/2 (980)	10 1/2 (265)	21 3/4 (550)	2 (51)	10 (255)																																																																																																																																																							
8135GT	35	70	03 (75)	7 (180)	4 3/4 (120)	49 1/2 (1257)	11 3/4 (300)	27 3/4 (705)	2 (51)	10 (255)																																																																																																																																																							
8150GT	50	100	03 (75)	10 (255)	6 (150)	49 1/2 (1257)	16 (405)	27 3/4 (705)	2 (51)	10 (255)																																																																																																																																																							
*Available with larger inlet and outlet when specified.																																																																																																																																																																	
NOTE: Whenever an interceptor is to be installed suspended in a floor slab with a cradle or independently, proper support is essential for safety and functional integrity of the installation. Supports / support system shall be of sufficient strength and proper design for the purpose intended and meet the approval of the architect and structural engineer. Jay R. Smith Mfg. Co. is not responsible for the design or recommendation of such supports. Upon request, Jay R. Smith Mfg. Co. will provide the weight of the specific unit. Additional weight must be added to compensate for the weight of the liquid / grease when full and in the flowing mode of operation. It is the responsibility of the installer to check all parts (internal and external) to verify they are in their proper operating order and location.																																																																																																																																																																	
REGULARLY FURNISHED: Steel Interceptor with Gray Duco Coating Inside and Outside with Steel Cone Draw-off Piping and Valve Line Shut-off Valve and Flow Control Fitting. VARIATIONS: ☐ NO-HUB Adaptor (2) Req'd (Specify Fig. 2646Y) NOTE: Dimensions shown in parentheses are in millimeters. OPTIONAL MATERIALS: ☐ Acid Resistant Coating Inside - ARI ☐ Acid Resistant Coating Outside - ARO ☐ Acid Resistant Coating Inside and Outside - ARIO ☐ Aluminum Cover - AC																																																																																																																																																																	
<table border="1" style="width:100%; border-collapse: collapse; font-size: 10px;"> <tr> <td style="width: 10%;">FIGURE NUMBER</td> <td style="width: 10%;">Q P N</td> <td style="width: 10%;">7-27-23 03/08/04 9-30-03</td> <td style="width: 20%;">Removed Function Updated Draw-off Valves Revised Table</td> <td style="width: 10%;">HS JJ RN</td> <td style="width: 10%;">CL CL CL</td> <td style="width: 10%;">WEIGHT POUNDS</td> <td style="width: 10%;">VOLUME CUBIC FEET</td> <td style="width: 20%; text-align: center;"> FIGURE NUMBER 8000GT SERIES </td> </tr> <tr> <td>REV.</td> <td>DATE</td> <td colspan="2">DESCRIPTION</td> <td>BY</td> <td>CKD. BY</td> <td></td> <td></td> <td></td> </tr> </table>								FIGURE NUMBER	Q P N	7-27-23 03/08/04 9-30-03	Removed Function Updated Draw-off Valves Revised Table	HS JJ RN	CL CL CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 8000GT SERIES	REV.	DATE	DESCRIPTION		BY	CKD. BY																																																																																																																																											
FIGURE NUMBER	Q P N	7-27-23 03/08/04 9-30-03	Removed Function Updated Draw-off Valves Revised Table	HS JJ RN	CL CL CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 8000GT SERIES																																																																																																																																																									
REV.	DATE	DESCRIPTION		BY	CKD. BY																																																																																																																																																												



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov