

N	 SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:				LOCATION																																																																																																																																																											
	GREASE INTERCEPTORS																																																																																																																																																															
	GREASE INTERCEPTORS WITH SEMI-AUTOMATIC DRAW-OFF FOR RECESSED INSTALLATION																																																																																																																																																															
WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA																																																																																																																																																																
<table border="1" style="width: 100%; border-collapse: collapse; font-size: 10px;"> <thead> <tr> <th rowspan="3">Fig. #</th> <th rowspan="3">GPM Flow Rate</th> <th rowspan="3">Grease Cap Lbs.</th> <th rowspan="3">Inlet and Outlet Size *A</th> <th colspan="6">Dimensions</th> <th rowspan="3">C.O. Plug Size G</th> <th rowspan="3">Line Shut-off Valve H</th> </tr> <tr> <th colspan="3">Roughing Dimensions</th> <th colspan="2">Body</th> </tr> <tr> <th>B</th> <th>C</th> <th>D</th> <th>Height E</th> <th>Width F</th> </tr> </thead> <tbody> <tr> <td>8007GTX</td> <td>07</td> <td>14</td> <td>02 (50)</td> <td>8 1/2 (215)</td> <td>3 1/2 (89)</td> <td>19 (485)</td> <td>12 (305)</td> <td>10 3/4 (275)</td> <td>2 (51)</td> <td>6 3/4 (175)</td> </tr> <tr> <td>8010GTX</td> <td>10</td> <td>20</td> <td>02 (50)</td> <td>9 1/2 (240)</td> <td>3 3/4 (95)</td> <td>21 1/4 (540)</td> <td>13 1/4 (335)</td> <td>13 (330)</td> <td>2 (51)</td> <td>6 3/4 (175)</td> </tr> <tr> <td>8015GTX</td> <td>15</td> <td>30</td> <td>02 (50)</td> <td>12 (305)</td> <td>3 1/2 (89)</td> <td>25 (635)</td> <td>15 1/2 (395)</td> <td>14 (355)</td> <td>2 (51)</td> <td>6 3/4 (175)</td> </tr> <tr> <td>8020GTX</td> <td>20</td> <td>40</td> <td>03 (75)</td> <td>13 (330)</td> <td>4 (100)</td> <td>28 1/2 (725)</td> <td>17 (430)</td> <td>15 3/4 (400)</td> <td>2 (51)</td> <td>10 (255)</td> </tr> <tr> <td>8025GTX</td> <td>25</td> <td>50</td> <td>03 (75)</td> <td>15 1/4 (390)</td> <td>4 1/2 (115)</td> <td>30 (760)</td> <td>19 3/4 (500)</td> <td>16 3/4 (425)</td> <td>2 (51)</td> <td>10 (255)</td> </tr> <tr> <td>8035GTX</td> <td>35</td> <td>70</td> <td>03 (75)</td> <td>16 (405)</td> <td>5 (125)</td> <td>32 1/2 (825)</td> <td>21 (535)</td> <td>18 1/4 (465)</td> <td>2 (51)</td> <td>10 (255)</td> </tr> <tr> <td>8050GTX</td> <td>50</td> <td>100</td> <td>03 (75)</td> <td>17 1/2 (445)</td> <td>6 3/4 (170)</td> <td>35 1/2 (900)</td> <td>24 1/4 (615)</td> <td>20 3/4 (525)</td> <td>2 (51)</td> <td>10 (255)</td> </tr> <tr> <td>8075GTX</td> <td>75</td> <td>150</td> <td>04 (100)</td> <td>21 1/2 (545)</td> <td>15 1/2 (395)</td> <td>50 (1270)</td> <td>37 (940)</td> <td>30 1/2 (775)</td> <td>3 (76)</td> <td>12 3/4 (325)</td> </tr> <tr> <td colspan="12" style="text-align: center; font-weight: bold;">LOW TYPE</td> </tr> <tr> <td>8120GTX</td> <td>20</td> <td>40</td> <td>03 (75)</td> <td>7 (180)</td> <td>3 1/2 (89)</td> <td>38 1/2 (980)</td> <td>10 1/2 (265)</td> <td>21 3/4 (550)</td> <td>2 (51)</td> <td>10 (255)</td> </tr> <tr> <td>8135GTX</td> <td>35</td> <td>70</td> <td>03 (75)</td> <td>7 (180)</td> <td>4 3/4 (120)</td> <td>49 1/2 (1257)</td> <td>11 3/4 (300)</td> <td>27 3/4 (705)</td> <td>2 (51)</td> <td>10 (255)</td> </tr> <tr> <td>8150GTX</td> <td>50</td> <td>100</td> <td>03 (75)</td> <td>10 (255)</td> <td>6 (150)</td> <td>49 1/2 (1257)</td> <td>16 (405)</td> <td>27 3/4 (705)</td> <td>2 (51)</td> <td>10 (255)</td> </tr> </tbody> </table>						Fig. #	GPM Flow Rate	Grease Cap Lbs.	Inlet and Outlet Size *A	Dimensions						C.O. Plug Size G	Line Shut-off Valve H	Roughing Dimensions			Body		B	C	D	Height E	Width F	8007GTX	07	14	02 (50)	8 1/2 (215)	3 1/2 (89)	19 (485)	12 (305)	10 3/4 (275)	2 (51)	6 3/4 (175)	8010GTX	10	20	02 (50)	9 1/2 (240)	3 3/4 (95)	21 1/4 (540)	13 1/4 (335)	13 (330)	2 (51)	6 3/4 (175)	8015GTX	15	30	02 (50)	12 (305)	3 1/2 (89)	25 (635)	15 1/2 (395)	14 (355)	2 (51)	6 3/4 (175)	8020GTX	20	40	03 (75)	13 (330)	4 (100)	28 1/2 (725)	17 (430)	15 3/4 (400)	2 (51)	10 (255)	8025GTX	25	50	03 (75)	15 1/4 (390)	4 1/2 (115)	30 (760)	19 3/4 (500)	16 3/4 (425)	2 (51)	10 (255)	8035GTX	35	70	03 (75)	16 (405)	5 (125)	32 1/2 (825)	21 (535)	18 1/4 (465)	2 (51)	10 (255)	8050GTX	50	100	03 (75)	17 1/2 (445)	6 3/4 (170)	35 1/2 (900)	24 1/4 (615)	20 3/4 (525)	2 (51)	10 (255)	8075GTX	75	150	04 (100)	21 1/2 (545)	15 1/2 (395)	50 (1270)	37 (940)	30 1/2 (775)	3 (76)	12 3/4 (325)	LOW TYPE												8120GTX	20	40	03 (75)	7 (180)	3 1/2 (89)	38 1/2 (980)	10 1/2 (265)	21 3/4 (550)	2 (51)	10 (255)	8135GTX	35	70	03 (75)	7 (180)	4 3/4 (120)	49 1/2 (1257)	11 3/4 (300)	27 3/4 (705)	2 (51)	10 (255)	8150GTX	50	100	03 (75)	10 (255)	6 (150)	49 1/2 (1257)	16 (405)	27 3/4 (705)	2 (51)	10 (255)
Fig. #	GPM Flow Rate	Grease Cap Lbs.	Inlet and Outlet Size *A	Dimensions						C.O. Plug Size G	Line Shut-off Valve H																																																																																																																																																					
				Roughing Dimensions								Body																																																																																																																																																				
				B	C	D	Height E	Width F																																																																																																																																																								
8007GTX	07	14	02 (50)	8 1/2 (215)	3 1/2 (89)	19 (485)	12 (305)	10 3/4 (275)	2 (51)	6 3/4 (175)																																																																																																																																																						
8010GTX	10	20	02 (50)	9 1/2 (240)	3 3/4 (95)	21 1/4 (540)	13 1/4 (335)	13 (330)	2 (51)	6 3/4 (175)																																																																																																																																																						
8015GTX	15	30	02 (50)	12 (305)	3 1/2 (89)	25 (635)	15 1/2 (395)	14 (355)	2 (51)	6 3/4 (175)																																																																																																																																																						
8020GTX	20	40	03 (75)	13 (330)	4 (100)	28 1/2 (725)	17 (430)	15 3/4 (400)	2 (51)	10 (255)																																																																																																																																																						
8025GTX	25	50	03 (75)	15 1/4 (390)	4 1/2 (115)	30 (760)	19 3/4 (500)	16 3/4 (425)	2 (51)	10 (255)																																																																																																																																																						
8035GTX	35	70	03 (75)	16 (405)	5 (125)	32 1/2 (825)	21 (535)	18 1/4 (465)	2 (51)	10 (255)																																																																																																																																																						
8050GTX	50	100	03 (75)	17 1/2 (445)	6 3/4 (170)	35 1/2 (900)	24 1/4 (615)	20 3/4 (525)	2 (51)	10 (255)																																																																																																																																																						
8075GTX	75	150	04 (100)	21 1/2 (545)	15 1/2 (395)	50 (1270)	37 (940)	30 1/2 (775)	3 (76)	12 3/4 (325)																																																																																																																																																						
LOW TYPE																																																																																																																																																																
8120GTX	20	40	03 (75)	7 (180)	3 1/2 (89)	38 1/2 (980)	10 1/2 (265)	21 3/4 (550)	2 (51)	10 (255)																																																																																																																																																						
8135GTX	35	70	03 (75)	7 (180)	4 3/4 (120)	49 1/2 (1257)	11 3/4 (300)	27 3/4 (705)	2 (51)	10 (255)																																																																																																																																																						
8150GTX	50	100	03 (75)	10 (255)	6 (150)	49 1/2 (1257)	16 (405)	27 3/4 (705)	2 (51)	10 (255)																																																																																																																																																						
*Available with larger inlet and outlet when specified.																																																																																																																																																																
NOTE: Whenever an interceptor is to be installed suspended in a floor slab with a cradle or independently, proper support is essential for safety and functional integrity of the installation. Supports / support system shall be of sufficient strength and proper design for the purpose intended and meet the approval of the architect and structural engineer. Jay R. Smith Mfg. Co. is not responsible for the design or recommendation of such supports. Upon request, Jay R. Smith Mfg. Co. will provide the weight of the specific unit. Additional weight must be added to compensate for the weight of the liquid / grease when full and in the flowing mode of operation. It is the responsibility of the installer to check all parts (internal and external) to verify they are in their proper operating order and location.																																																																																																																																																																
REGULARLY FURNISHED: Steel Interceptor with Gray Duco Coating Inside and Outside with Steel Cone, Draw-off Hose and Cap, Line Shut-off Valve and Flow Control Fitting. VARIATIONS: ☐ NO-HUB Adaptor (2) Req'd (Specify Fig. 2646Y) NOTE: Dimensions shown in parentheses are in millimeters. OPTIONAL MATERIALS: ☐ Acid Resistant Coating Inside - ARI ☐ Acid Resistant Coating Outside - ARO ☐ Acid Resistant Coating Inside and Outside - ARIO ☐ Aluminum Cover - AC																																																																																																																																																																
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td rowspan="2" style="width: 30px; text-align: center; vertical-align: middle;">FIGURE NUMBER</td> <td style="width: 40px; text-align: center;">N</td> <td style="width: 60px; text-align: center;">7-27-23</td> <td rowspan="2" style="width: 150px; text-align: center;">Removed Function Revised Table Revised Table Submittal Redraw Illustrator</td> <td style="width: 40px; text-align: center;">HS</td> <td rowspan="2" style="width: 40px; text-align: center;">CL</td> <td rowspan="2" style="width: 60px; text-align: center;">WEIGHT POUNDS</td> <td rowspan="2" style="width: 60px; text-align: center;">VOLUME CUBIC FEET</td> <td rowspan="2" style="width: 100px; text-align: center;">FIGURE NUMBER</td> </tr> <tr> <td style="text-align: center;">M</td> <td style="text-align: center;">9-30-03</td> <td style="text-align: center;">RN</td> <td style="text-align: center;">CL</td> <td rowspan="2" style="text-align: center; font-size: 24px; font-weight: bold;">8000GTX SERIES</td> </tr> <tr> <td></td> <td style="text-align: center;">L</td> <td style="text-align: center;">3-9-01</td> <td></td> <td style="text-align: center;">RN</td> <td style="text-align: center;">AM</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">K</td> <td style="text-align: center;">07-22-99</td> <td></td> <td style="text-align: center;">JJ</td> <td style="text-align: center;">BS</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">REV.</td> <td style="text-align: center;">DATE</td> <td style="text-align: center;">DESCRIPTION</td> <td style="text-align: center;">BY</td> <td style="text-align: center;">CKD. BY</td> <td></td> <td></td> <td></td> </tr> </table>						FIGURE NUMBER	N	7-27-23	Removed Function Revised Table Revised Table Submittal Redraw Illustrator	HS	CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER	M	9-30-03	RN	CL	8000GTX SERIES		L	3-9-01		RN	AM					K	07-22-99		JJ	BS					REV.	DATE	DESCRIPTION	BY	CKD. BY																																																																																																																					
FIGURE NUMBER	N	7-27-23	Removed Function Revised Table Revised Table Submittal Redraw Illustrator	HS	CL		WEIGHT POUNDS	VOLUME CUBIC FEET		FIGURE NUMBER																																																																																																																																																						
	M	9-30-03		RN		CL			8000GTX SERIES																																																																																																																																																							
	L	3-9-01		RN	AM																																																																																																																																																											
	K	07-22-99		JJ	BS																																																																																																																																																											
	REV.	DATE	DESCRIPTION	BY	CKD. BY																																																																																																																																																											



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov