

H	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:				LOCATION	
	SPECIAL PURPOSE DRAINS STAINLESS STEEL - CARBON STEEL					
	INTEGRAL TRAP DRAIN WITH FLOOR LEVEL CLEANOUT					
	Free Area 20.50 SQ IN (132) SQ CM Design Pressures and Temperatures 1. With proper outlet connection, shall be watertight up to 10 ft. of water column (4.34 psig). 2. When exposed to effluent appropriate for drain material, the drain shall withstand effluent temperatures of 180 degrees F at ambient pressure. ☐ Fig. 9750S SPIGOT OUTLET Δ add 1/4"(6) when Nickel Bronze Top is specified. REGULARLY FURNISHED: CF8 (Equivalent to Type 304) Rough Finish Stainless Steel Body, Loose Set Non-Tilt Grate and Cleanout Plug with Gasket. VARIATIONS: ☐ 4(100) or 6"(150) Dia. Funnel (Specify Fig. 9703) ☐ 8 3/4(220) x 3 3/4"(95) Funnel (Specify Fig. 9704) ☐ Auxiliary Inlet -N2 ☐ Bronze Backwater Valve -BWV ** ☐ Stainless Steel Backwater Valve -BWV** ☐ Steel Spanner Wrench for C.O. -SW ☐ Vandal Proof Grate -U ☐ BW Butt Weld Outlet (Specify Schedule -S05, -S10, -S40 or -S80) OPTIONAL MATERIALS: ☐ A-27 Carbon Steel -A27 ☐ CF8M (Equivalent to Type 316) Stainless Steel -316 ☐ Nickel Bronze Frame, Grate and Cleanout Cover -NB ** NOTE: These valves offer protection against backwater surges. Backflow is prevented when not obstructed by debris or sludge. Use for gravity flow only, not pressurized application.					
9750	FIGURE NUMBER 9750					



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov