

R	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: LOCATION 						
	WATER DAM TYPE ROOF DRAIN WITH ADJUSTABLE OVERFLOW AND PROTECTIVE DOME						
DRAWING NUMBER S1072	SIZE A	SCALE: NONE	DATE: 5-17-66	APPROVED BY: BS	CHECKED BY: BS	DRAWN BY: WN	A (Pipe Size) = 02(50), 03(75) or 04(100) ☐ Fig. 1072C CAULK OUTLET ☐ Fig. 1072Y NO-HUB OUTLET ▲ This Dimension to Internal Stop of Speedi-set® Gasket. REGULARLY FURNISHED: Duco Cast Iron Body, Combined Flashing Collar and Gravel Stop with Adjustable Standpipe and Dome. VARIATIONS: ☐ Extension (Specify Height) -E ☐ Secondary Flashing Clamp -C2 ☐ Underdeck Clamp -C ☐ Sump Receiver -R For Side Outlet See Fig. 1075 OPTIONAL MATERIALS: ☐ All Galvanized -G ☐ Bronze Dome -RBD ☐ Aluminum Dome -AD

NOTE: 02(50), 03(75) & 04(100) sizes require a transition collar (not shown in above illustration) which fits between the body & collar.

NOTE: Dimensions shown in parentheses are in millimeters.



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov